


Product datasheet

Specifications



rotary handle left side GS1 - 32 A - red handle

GS1AH321

ⓘ Discontinued

Main

| | |
|---------------------------|-------------------------------|
| Range of product | TeSys GS |
| Device short name | GS1 handle |
| Product or component type | Handle |
| Product compatibility | Switch disconnecter 50...63 A |
| Type of operating handle | External |
| Mounting location | Left |
| Handle colour | Red |

Complementary

| | |
|---------------------------|---------|
| Handle front plate colour | Yellow |
| Rotary handle padlocking | With |
| Net weight | 1600 kg |

Environment

| | |
|-------------------------|------|
| IP degree of protection | IP65 |
|-------------------------|------|

Contractual warranty

| | |
|----------------------|----|
| Warranty (in months) | 18 |
|----------------------|----|

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Longer



Lifetime extension

Repair

No

Use Again



Repack and remanufacture

WEEE Label



The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins