

Product datasheet

Specifications



blown fuse indicator 1NO 1NC standard - for ISFT160

49892

⚠ Discontinued on: 2 Jul 2024

⚠ Discontinued

Main

Range of product	ISFT160
Range	FuPact
Device short name	blown fuse indicator
Product or component type	Blown Fuse Indicator
Device application	Display
Range compatibility	FuPact FuPacT ISFT fuse-switch disconnecter
Poles description	3P
Signal contacts composition	1 NO 1 NC

Complementary

Auxiliary contacts type	Standard
[Ith] conventional free air thermal current	6 A
[Ie] rated operational current	1 A at 48 V 3 A at 24 V 6 A at 110 V 50/60 Hz 6 A at 220/240 V 50/60 Hz 6 A at 24 V 50/60 Hz 6 A at 48 V 50/60 Hz 0.25 A at 220/240 V 0.5 A at 110 V
Minimum load	100 mA at 24 V

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	6 cm
Package 1 Width	12 cm
Package 1 Length	20 cm
Package 1 Weight	42 g

Contractual warranty

Warranty (in months)	18
----------------------	----

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Longer

Lifetime extension	
Repair	No

Use Again

Repack and remanufacture	
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins