

Product data sheet

Specifications



ASCO 4900 Load Bank

ASCOLBLV4900

⚠ Discontinued on: Nov 20, 2023

⚠ Discontinued

Main

Product Type Resistive load bank

Complementary

Voltage Rating 400 V AC 50 Hz, 3 phase
480 V AC 60 Hz, 3 phase
600 V AC 60 Hz, 3 phase

Capacity Rating 1000 kW
1500 kW
2000 kW
2250 kW
2500 kW

Load Step Resolution 5 kW
50 kW

Cooling System Rating 20646604.4 Gal/hr(US) (78154.5 m3/h)

Provided Equipment Switch 3 On-Off
LED 2 on
LED 1 alarm indication
Fuse
Cooling fans

Enclosure Material Aluminium
Steel

Surface Finish Polyester powder

Color Gray

Connection Terminals Terminals inside)

Length 89.7 in (2278 mm)

Width 75.2 in (1911 mm)

Height 93.1 in (2365 mm)

Product Weight 3600.2 lb(US) (1633 kg)

Environment

Ambient Air Temperature -18...122 °F (-28...50 °C)

Standards ISO 9001
NEMA

Contractual warranty

Warranty (in months) 18

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

Materials and Substances

Packaging made with recycled cardboard **Yes**

Packaging without single use plastic **No**

Use Longer

Lifetime extension

Repair **No**