

Product data sheet

Specifications



ASCO 9200 Load Bank

ASCOLBLV9200

⚠ Discontinued on: Nov 20, 2023

⚠ Discontinued

Main

Product Type	Resistive load bank
--------------	---------------------

Complementary

Capacity Rating	1000 kW
	2000 kW
	3000 kW
	3500 kW
Load Step Resolution	500 kW
Voltage Rating	4160 V AC 60 Hz
	12470 V AC 60 Hz
	13200 V AC 60 Hz
	13800 V AC 60 Hz
Number of Phases	3 phase
Resistor Load Tolerance	5 %
Cooling System Rating	8976779.9 Gal/hr(US) (33980.2 m3/h)
Ambient Air Temperature	-18...122 °F (-28...50 °C)
Provided Equipment	Switch 3 On-Off
	LED 2 on
	LED 1 alarm indication
	Voltage transformer 1 inside the enclosure
	Cooling fans inside the enclosure
Connection Terminals	Terminals front panel)
Enclosure Material	Stainless steel
Color	Gray
Width	101.0 in (2565 mm)
Product Weight	9239.6 lb(US) (4191 kg)

Environmental

Standards	NEMA
	ISO 9001

Contractual warranty

Warranty (in months)	18
----------------------	----

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

Materials and Substances	
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No

Use Longer

Lifetime extension	
Repair	No