



XY2CZ917

Mounting kits					
Contents	For use with	Cable diameter in. (mm)	Length of cable ft (m)	Reference	Weight lb (kg)
1 tensioner + 1 bracket	XY2CE	–	–	XY2CZ917	1.349 (0.612)
1 spring tensioner + 1 notched washer + 1 circlip	XY2CH	–	–	XY2CZ918	0.022 (0.010)
1 galvanized cable + 1 cable grip XY2CZ523 + 1 end spring XY2CZ703 (1)	XY2CH and XY2CJ	0.13 (3.2)	32.8 (10)	XY2CZ9310	0.915 (0.415)
			49.2 (15)	XY2CZ9315	1.179 (0.535)
			60.7 (18.5)	XY2CZ9318	1.280 (0.580)
1 galvanized cable + 4 cable grips XY2CZ523 + 1 turnbuckle XY2CZ404 + 1 cable support XY2CZ601 + 3 cable end protectors XY2CZ701 + 1 end spring XY2CZ702 (1)	XY2CE, XY2CH, and XY2CJ	0.13 (3.2)	82.0 (25)	XY2CZ9325	2.756 (1.250)
			98.4 (30)	XY2CZ9330	2.866 (1.300)
1 galvanized cable + 4 cable grips XY2CZ524 + 1 turnbuckle XY2CZ404 , + 1 cable support XY2CZ601 + 3 cable end protectors XY2CZ704 + 1 end spring XY2CZ702 (1)	XY2CE	0.13 (3.2)	164.0 (50)	XY2CZ9350	4.365 (1.980)
			82.0 (25)	XY2CZ9525	4.200 (1.905)
			164.0 (50)	XY2CZ9550	7.231 (3.280)
			230 (70)	XY2CZ9570	8.180 (4.000)

(1) The use of an end spring is strongly recommended, especially when using longer lengths of cable.

Note: For the maximum cable length, we recommend using

- 3.2 mm diameter galvanized cables for the XY2CH range
- 5 mm diameter galvanized cables for the XY2CE range