

# Product data sheet

Specifications



## EasyPact TVS contactor 3P(3 NO) - AC-3 - $\leq 440$ V 9A - 24 V AC coil

LC1E0901B6

⚠ Discontinued on: May 19, 2023

⚠ Discontinued

### Main

Range	Easy TeSys
Range of product	Easy TeSys Control
Product or component type	Contactor
Device short name	LC1E
Contactor application	Motor control Resistive load
Utilisation category	AC-3 AC-3e AC-1
Poles description	3P
[Ue] rated operational voltage	Power circuit: $\leq 690$ V AC 50/60 Hz
[Ie] rated operational current	9 A (at $<55$ °C) at $\leq 440$ V AC AC-3 for power circuit 9 A (at $<55$ °C) at $\leq 440$ V AC AC-3e for power circuit 25 A (at $<55$ °C) at $\leq 440$ V AC AC-1 for power circuit
[Uc] control circuit voltage	24 V AC 60 Hz

### Complementary

Motor power kW	2.2 kW at 220/230 V AC 50/60 Hz 4 kW at 380/400 V AC 4 kW at 415/440 V AC 4 kW at 500 V AC 4 kW at 660/690 V AC 5.5 kW at 660...690 V
Pole contact composition	3 NO
[Ith] conventional free air thermal current	25 A (at 55 °C) for power circuit
Irms rated making capacity	117 A at 440 V AC for power circuit conforming to IEC 60947-4-1
Rated breaking capacity	76.5 A at 440 V for power circuit conforming to IEC 60947
[Icw] rated short-time withstand current	105 A 40 °C - 10 s for power circuit 61 A 40 °C - 60 s for power circuit 30 A 40 °C - 600 s for power circuit
Associated fuse rating	20 A gG at $\leq 690$ V coordination type 1 for power circuit 10 A gG at $\leq 690$ V for auxiliary contact circuit conforming to IEC 60947-5-1
Average impedance	2.5 mOhm - Ith 25 A 50 Hz for power circuit
Power dissipation per pole	0.2 W AC-3 1.6 W AC-1
[Ui] rated insulation voltage	690 V conforming to IEC 60947-4-1
Overvoltage category	III

List Price displayed is VAT EXCLUSIVE.

<b>Pollution degree</b>	3
<b>[Uimp] rated impulse withstand voltage</b>	6 kV coil not connected to the power circuit conforming to IEC 60947
<b>Mechanical durability</b>	10000000 cycles
<b>Electrical durability</b>	1400000 cycles AC-3 150000 cycles AC-1
<b>Control circuit type</b>	AC at 60 Hz
<b>Control circuit voltage limits</b>	0.85...1.1 U <sub>c</sub> (-5...55 °C):operational 60 Hz 0.3...0.6 U <sub>c</sub> (-5...55 °C):drop-out 60 Hz
<b>Inrush power in VA</b>	95 VA 50 Hz cos phi 0.75 (at 20 °C) 95 VA 60 Hz cos phi 0.75 (at 20 °C)
<b>Hold-in power consumption in VA</b>	8.3 VA 50 Hz cos phi 0.3 (at 20 °C) 8.5 VA 60 Hz cos phi 0.3 (at 20 °C)
<b>Heat dissipation</b>	2...3 W for control circuit
<b>Operating time</b>	12...22 ms on closing 4...19 ms on opening
<b>Maximum operating rate</b>	1800 cyc/h 60 °C
<b>Connections - terminals</b>	Power circuit: screw clamp terminals 1 1...4 mm <sup>2</sup> - cable stiffness: flexible without cable end Power circuit: screw clamp terminals 2 1...2.5 mm <sup>2</sup> - cable stiffness: flexible without cable end Power circuit: screw clamp terminals 1 1...4 mm <sup>2</sup> - cable stiffness: flexible with cable end Power circuit: screw clamp terminals 2 1...4 mm <sup>2</sup> - cable stiffness: flexible with cable end Power circuit: screw clamp terminals 1 1...4 mm <sup>2</sup> - cable stiffness: solid without cable end Power circuit: screw clamp terminals 2 1...4 mm <sup>2</sup> - cable stiffness: solid without cable end Control circuit: screw clamp terminals 1 1...4 mm <sup>2</sup> - cable stiffness: flexible without cable end Control circuit: screw clamp terminals 2 1...2.5 mm <sup>2</sup> - cable stiffness: flexible without cable end Control circuit: screw clamp terminals 1 1...4 mm <sup>2</sup> - cable stiffness: flexible with cable end Control circuit: screw clamp terminals 2 1...4 mm <sup>2</sup> - cable stiffness: flexible with cable end Control circuit: screw clamp terminals 1 1...4 mm <sup>2</sup> - cable stiffness: solid without cable end Control circuit: screw clamp terminals 2 1...4 mm <sup>2</sup> - cable stiffness: solid without cable end
<b>Tightening torque</b>	Power circuit: 1.2 N.m Control circuit: 1.2 N.m
<b>Auxiliary contact composition</b>	1 NC
<b>Minimum switching voltage</b>	17 V for auxiliary contact circuit
<b>Minimum switching current</b>	5 mA for auxiliary contact circuit
<b>Insulation resistance</b>	> 10 MOhm for auxiliary contact circuit
<b>Non-overlap time</b>	1.5 ms on energisation guaranteed between NC and NO contact 1.5 ms on de-energisation guaranteed between NC and NO contact
<b>Mounting support</b>	Plate DIN rail

## Environment

<b>Standards</b>	EN/IEC 60947-1 EN/IEC 60947-4-1 EN/IEC 60947-5-1 GB/T 14048.1 GB/T 14048.4 GB/T 14048.5 EN/IEC 60335-1:Clause 30.2 EN/IEC 60335-2-40:Annex JJ IS/IEC 60947-1 IS/IEC 60947-4-1 IS/IEC 60947-5-1
<b>Product certifications</b>	CB Scheme CCC CE EAC BIS
<b>IP degree of protection</b>	IP2X conforming to IEC 60529
<b>Protective treatment</b>	TH (pollution degree 3) conforming to IEC 60068-2-30
<b>Permissible ambient air temperature around the device</b>	-20...70 °C at Uc -60...80 °C storage -5...55 °C operation
<b>Operating altitude</b>	3000 m without derating
<b>Fire resistance</b>	850 °C conforming to IEC 60695-2-1
<b>Mechanical robustness</b>	Vibrations contactor open (1.5 Gn, 5...300 Hz) Vibrations contactor closed (3 Gn, 5...300 Hz) Shocks contactor open (7 Gn for 11 ms) Shocks contactor closed (10 Gn for 11 ms)
<b>Height</b>	74 mm
<b>Width</b>	45 mm
<b>Depth</b>	80 mm
<b>Product weight</b>	0.3 kg

## Packing Units

<b>Unit Type of Package 1</b>	PCE
<b>Number of Units in Package 1</b>	1
<b>Package 1 Height</b>	8.31 cm
<b>Package 1 Width</b>	7.4 cm
<b>Package 1 Length</b>	4.82 cm
<b>Package 1 Weight</b>	340 g
<b>Unit Type of Package 2</b>	S02
<b>Number of Units in Package 2</b>	36
<b>Package 2 Height</b>	15 cm
<b>Package 2 Width</b>	30 cm
<b>Package 2 Length</b>	40 cm
<b>Package 2 Weight</b>	12.648 kg

## Contractual warranty

<b>Warranty (in months)</b>	18
-----------------------------	----



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



### Environmental footprint

Environmental Disclosure

[Product Environmental Profile](#)

## Use Better



### Materials and Substances

EU RoHS Directive

[Compliant](#)

## Use Longer



### Lifetime extension

Repair

No

## Use Again



### Repack and remanufacture

WEEE Label



The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins