


Product datasheet

Specifications



MH3 servomotor, 140mm, 1 stack,
smooth Shaft, SinCos Singleturn
128, Brake, angular, IP65

MH31401P01F2200

⚠ Discontinued on: 30 Aug 2022

⚠ Discontinued

Main

Range compatibility	PacDrive 3
Device short name	MH3
Product or component type	Servo motor

Complementary

Maximum mechanical speed	4000 rpm
[Us] rated supply voltage	115...480 V
Network number of phases	Three phase
Continuous stall current	8.58 A
Continuous stall torque	10.3 N.m, 115...480 V, three phase
Continuous power	2640 W
Peak stall torque	39.9 N.m, 115...480 V, three phase
Nominal output power	0.98 W, 115 V 1.78 W, 230 V 2.64 W, 400 V 2.64 W, 480 V
Nominal torque	9.36 N.m for LXM52 at 7.82 mA, 115 V, three phase 8.5 N.m for LXM52 at 7.3 mA, 230 V, single phase 7.22 N.m for LXM52 at 6.35 mA, 400 V, three phase 7.22 N.m for LXM52 at 6.35 mA, 480 V, three phase 9.36 N.m for LXM62 at 7.82 mA, 115 V, single phase 8.5 N.m for LXM62 at 7.3 mA, 230 V, single phase 7.22 N.m for LXM62 at 6.35 mA, 400 V, three phase 7.22 N.m for LXM62 at 6.35 mA, 480 V, three phase
Nominal speed	1000 rpm for LXM52 at 7.82 mA, 115 V, single phase 2000 rpm for LXM52 at 7.3 mA, 230 V, single phase 3500 rpm for LXM52 at 6.35 mA, 400 V, three phase 3500 rpm for LXM52 at 6.35 mA, 480 V, three phase 1000 rpm for LXM62 at 7.82 mA, 115 V, single phase 2000 rpm for LXM62 at 7.3 mA, 230 V, single phase 3500 rpm for LXM62 at 6.35 mA, 400 V, three phase 3500 rpm for LXM62 at 6.35 mA, 480 V, three phase
Maximum current Irms	29.8 A
Shaft end	Smooth shaft
Second shaft	Without second shaft end
Shaft diameter	24 mm
Shaft length	50 mm
IP degree of protection	IP65 standard
Encoder type	Single turn SinCos Hiperface

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Speed feedback resolution	128 periods
Holding brake	With
Holding torque	18 N.m
Mounting support	International standard flange
Motor flange size	140 mm
Electrical connection	Rotatable right-angled connectors
Torque constant	1.2 N.m/A at 120 °C
Back emf constant	77.41 V/krpm
Number of motor poles	10
Rotor inertia	17.96 kg.cm ²
Stator resistance	0.69 Ohm
Stator inductance	6.72 mH
Stator electrical time constant	9.7 ms
Maximum radial force Fr	1930 N at 1000 rpm 1530 N at 2000 rpm 1340 N at 3000 rpm
Brake pull-in power	18 W
Type of cooling	Natural convection
Length	187 mm
Centring collar diameter	130 mm
Centring collar depth	3.5 mm
Number of mounting holes	4
Mounting holes diameter	11 mm
Circle diameter of the mounting holes	165 mm
Product weight	10.3 kg
Sizing reference	MH31401P
Temperature copper hot	135 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	26.0 cm
Package 1 Width	20.0 cm
Package 1 Length	59.0 cm
Package 1 Weight	9.3 kg

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

Materials and Substances	
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Compliant By Exemption
REACH Regulation	Reference contains Substances of Very High Concern above the threshold
PVC free	Yes

Use Longer

Lifetime extension	
Repair	No

Use Again

Repack and remanufacture	
End of life manual availability	No need of specific recycling operations
Take-back	No