


Product datasheet

Specifications



External rotary handle, TeSys GS,
black handle, right side mounting, 2
positions I-O, IP65, for GS
100-400A IEC

GS1AH230

! Discontinued

Main

Range of product	TeSys
Range	TeSys
Device short name	GS1AH
Product or component type	Rotary handle
Range compatibility	TeSys TeSys GS GS1 J TeSys TeSys GS GS1 K TeSys TeSys GS GS1 L TeSys TeSys GS GS1 N TeSys TeSys GS GS1P TeSys TeSys GS GS1Q
Type of operating handle	External right side
Handle colour	Black
Handle front plate colour	Black

Complementary

Handle positions	O-I
Rotary handle padlocking	Lockable in O position
Switch rated current	100 A 125 A 160 A 200 A 250 A 315 A 400 A
Standards	IEC

Environment

IP degree of protection	IP65
-------------------------	------

Contractual warranty

Warranty (in months)	18
----------------------	----

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Longer



Lifetime extension

Repair

No

Use Again



Repack and remanufacture

WEEE Label



The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins