

Product data sheet

Specifications



Circuit breaker frame, MasterPact MTZ1 16H3 fixed for MicroLogic X, 1600A, 66kA/415VAC (Icu), 3P

LV846440

Main

Range	MasterPacT
Product name	MasterPact MTZ1
Device short name	MTZ1 16 H3
Product or Component Type	Circuit breaker
Device Application	Power distribution protection
Poles description	3P
Control type	Without control unit
Product compatibility	control unit MicroLogic 2.0 X control unit MicroLogic 5.0 X control unit MicroLogic 6.0 X control unit MicroLogic 7.0 X control unit MicroLogic 2.0 Xi control unit MicroLogic 5.0 Xi control unit MicroLogic 6.0 Xi control unit MicroLogic 7.0 Xi
Line Rated Current	1600 A 104 °F (40 °C)
Breaking capacity code	H3 66 kA 415 V AC
[Ue] rated operational voltage	690 V AC 50/60 Hz
Suitability for isolation	Yes EN/IEC 60947-2
Selectivity category	Category B
Control Type	Push-button
Mounting Mode	Fixed

Complementary

Breaking capacity	66 kA 220/415 V AC 50/60 Hz 66 kA 440 V AC 50/60 Hz
[Ics] rated service breaking capacity	50 kA 440 V AC 50/60 Hz 50 kA 220/415 V AC 50/60 Hz
[Icw] rated short-time withstand current	30 kA 3 s 50 kA 1 s 50 kA 0.5 s
[Icm] rated short-circuit making capacity	145 kA 220/415 V AC 50/60 Hz 145 kA 440 V AC 50/60 Hz
Integrated instantaneous protection (DIN in kA peak)	94.5...115.5 kA
Sensor rating	1600 A 630 A 1250 A 400 A 800 A 1000 A

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

[Ui] rated insulation voltage	1000 V AC 50/60 Hz
[Uimp] rated impulse withstand voltage	12 kV
Power dissipation in W	220 W
Maximum breaking time	25 ms
Maximum closing response time	50 ms
Mounting Support	Rails Base plate
Upside connection	Front Rear
Downside connection	Front Rear
Connection pitch	2.8 in (70 mm)
Mechanical durability	10000 cycles with periodic preventive maintenance
Electrical durability	6000 cycles 440 V AC 50/60 Hz at In EN/IEC 60947-2 AC-23A 6000 cycles 440 V AC 50/60 Hz at In EN/IEC 60947-3 AC-3 6000 cycles 440 V AC 50/60 Hz at In EN/IEC 60947-3
Height	11.9 in (301 mm)
Width	10.9 in (276 mm)
Depth	8.2 in (209 mm)
Product Weight	30.9 lb(US) (14 kg)
Standards	EN/IEC 60947-1 EN/IEC 60947-2 EN/IEC 60947-2 Annex H IEC 61557-12
Product Certifications	CE IECEE CB Scheme

Environment

IP degree of protection	IP30 conforming to EN 60529
Pollution degree	3 IEC 60947-1
Ambient air temperature for operation	-13...158 °F (-25...70 °C)
Ambient Air Temperature for Storage	-40...185 °F (-40...85 °C)
Operating altitude	0...6561.68 ft (0...2000 m) without derating 2000...5000 m with derating

Ordering and shipping details

GTIN	3606481155337
------	---------------

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	11.8 in (30.0 cm)
Package 1 Width	11.8 in (30.0 cm)
Package 1 Length	15.7 in (40.0 cm)
Package weight(Lbs)	33.07 lb(US) (15.0 kg)

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	1 436 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	160 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	4 kg CO2 eq.
Carbon footprint of the installation phase [A5]	16 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	1 211 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	45 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile

Use Better



Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No, we have minimized the use of plastic in the packaging in compliance with regulations and considering quality and safety standards
SCIP Number	44ce05ea-25e9-435c-886d-b1162ae4666b
EU RoHS Directive	Compliant By Exemption
REACH Regulation	Reference contains Substances of Very High Concern above the threshold
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
Halogen content performance	Product contains halogen above thresholds
PVC free	No
Silicon free	No

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Recyclability potential, in %	73
Circularity Profile	End of Life Information

Take-back	No
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.