

Product datasheet

Specifications



servo motor BSH, Lexium 15,
88N.m, 2000rpm, 205mm, untapped
shaft, Sincos single turn, without
brake, IP65

BSH2053P21A3A

! Discontinued

! End-of-service on: 13 Jan 2021

Main

| | |
|---------------------------|---|
| Device short name | BSH |
| Product or component type | Servo motor |
| Maximum mechanical speed | 3800 rpm |
| Continuous stall torque | 88 N.m for LXM15HC20N4X, 400 V, three phase 88 N.m for LXM15HC20N4X, 480 V, three phase 90 N.m for LXM15HC20N4X, 230 V, three phase |
| Peak stall torque | 330 N.m for LXM15HC20N4X, 480 V, three phase 330 N.m for LXM15HC20N4X, 400 V, three phase 202.96 N.m for LXM15HC20N4X, 230 V, three phase |
| Nominal output power | 7400 W for LXM15HC20N4X, 230 V, three phase 9400 W for LXM15HC20N4X, 400 V, three phase 9400 W for LXM15HC20N4X, 480 V, three phase |
| Nominal torque | 45 N.m for LXM15HC20N4X, 400 V, three phase 45 N.m for LXM15HC20N4X, 480 V, three phase 70.45 N.m for LXM15HC20N4X, 230 V, three phase |
| Nominal speed | 1000 rpm for LXM15HC20N4X, 230 V, three phase 2000 rpm for LXM15HC20N4X, 400 V, three phase 2000 rpm for LXM15HC20N4X, 480 V, three phase |
| Product compatibility | LXM15HC20N4X at 230 V three phase LXM15HC20N4X at 400 V three phase LXM15HC20N4X at 480 V three phase |
| Shaft end | Untapped |
| IP degree of protection | IP65 standard IP67 with IP67 kit |
| Speed feedback resolution | 131072 points/turn |
| Holding brake | Without |
| Mounting support | International standard flange |
| Electrical connection | Power connection terminal Rotatable right-angled connectors |

Complementary

| | |
|--------------------------|--------------------------|
| Range compatibility | Lexium 15 |
| supply voltage max | 480 V |
| Network number of phases | Three phase |
| Continuous stall current | 31.9 A |
| maximum continuous power | 2.5 W |
| Maximum current Irms | 136.1 A for LXM15HC20N4X |

| | |
|---------------------------------------|--|
| Maximum permanent current | 136.1 A |
| Second shaft | Without second shaft end |
| Shaft diameter | 38 mm |
| Shaft length | 80 mm |
| Feedback type | Single turn SinCos Hiperface |
| Motor flange size | 205 mm |
| Number of motor stacks | 3 |
| Torque constant | 2.76 N.m/A at 120 °C |
| Back emf constant | 172 V/krpm at 120 °C |
| Rotor inertia | 182 kg.cm ² |
| Stator resistance | 0.2 Ohm at 20 °C |
| Stator inductance | 4.2 mH at 20 °C |
| Stator electrical time constant | 21 ms at 20 °C |
| Maximum radial force Fr | 3120 N at 3000 rpm 3570 N at 2000 rpm 4500 N at 1000 rpm |
| Maximum axial force Fa | 0.2 x Fr |
| Type of cooling | Natural convection |
| Length | 489 mm |
| Centring collar diameter | 180 mm |
| Centring collar depth | 4 mm |
| Number of mounting holes | 4 |
| Mounting holes diameter | 14 mm |
| Circle diameter of the mounting holes | 215 mm |
| Product weight | 67 kg |
| Sizing reference | BSH2053P |
| Network number of phases | 3 |
| Accuracy error [angular] | 1.4 ° |
| Temperature copper hot | 120 °C |
| Temperature magnet hot | 100 °C |
| Temperature magnet rt | 20 °C |

Packing Units

| | |
|------------------------------|-------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 41 cm |
| Package 1 Width | 31 cm |
| Package 1 Length | 72 cm |
| Package 1 Weight | 69 kg |

Contractual warranty

| | |
|----------------------|----|
| Warranty (in months) | 18 |
|----------------------|----|



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Longer



Lifetime extension

Repair

No