

Product datasheet

Specifications



C60 - earth leakage add-on block - Vigi C60 - 3P - 25A - 30mA

26751

 **Discontinued on:** 29 Apr 2019

 **Discontinued**

Main

Product or component type	Add-on residual current device
Device short name	Vigi C60
Poles description	3P
[In] rated current	25 A
Network type	AC
Earth-leakage sensitivity	30 mA
Earth-leakage protection time delay	Instantaneous
Earth-leakage protection class	Type A-SI (Super Immunised)
Standards	IEC 60947-2

Complementary

Device location in system	Outgoer
Network frequency	50/60 Hz
[Ue] rated operational voltage	220...415 V AC 50/60 Hz
Residual current tripping technology	Voltage dependent
[Ui] rated insulation voltage	500 V AC 50/60 Hz conforming to IEC 60947-2
[Uimp] rated impulse withstand voltage	6 kV conforming to IEC 60947-2
Mounting support	35 mm symmetrical DIN rail
Electrical connection to mcb	By screws
9 mm pitches	6
Height	87 mm
Width	108 mm
Depth	74 mm
Net weight	0.18 kg
Mechanical durability	20000 cycles
Connections - terminals	Tunnel type terminals 0.5...16 mm ² flexible Tunnel type terminals 0.5...25 mm ² rigid
Wire stripping length	14 mm
Tightening torque	2 N.m

Environment

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Pollution degree	3 conforming to IEC 60947-2
Tropicalisation	2 conforming to IEC 60947-2
Relative humidity	95 % at 55 °C
Operating altitude	2000 m
Ambient air temperature for operation	-25...60 °C
Ambient air temperature for storage	-40...70 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	8 cm
Package 1 Width	9.2 cm
Package 1 Length	14.9 cm
Package 1 Weight	0.216 kg



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Longer

Lifetime extension	
Repair	No

Use Again

Repack and remanufacture	
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins