


Product datasheet

Specifications



bar-mounted contactor - TeSys LC1-BR - 1 pole - AC-1 440V 2750 A - coil 400V AC

LC1BR31V40

⚠ Discontinued on: 1 Aug 2024

⚠ Discontinued

Main

Range	TeSys
Product name	TeSys B
Product or component type	Contactors
Device short name	LC1BR
Contactors application	Motor-heating-lighting
Utilisation category	AC-1
Control circuit type	AC
Coil type	Standard
Poles description	1P
Pole contact composition	1 NO
[Ie] rated operational current	2750 A (at <40 °C) AC AC-1 for power circuit
Auxiliary contact composition	4 NO
[Uc] control circuit voltage	400 V AC 50...400 Hz

Complementary

Control circuit voltage limits	Drop-out: 0.4...0.5 Uc at 50...400 Hz Operational: 0.85...1.1 Ucw at 50...400 Hz
[Ui] rated insulation voltage	1000 V - for power circuit conforming to IEC 60158-1 1000 V - for power circuit conforming to IEC 60947-4 1500 V - for power circuit conforming to VDE 0110 group C
Mounting mode	Fixed
Mounting support	Notched mounting rails Bar support bracket
Connections - terminals	Power circuit: bars 4 x - busbar cross section: 100 x 5 mm
Tightening torque	Power circuit: 35 N.m - on bars
[Ue] rated operational voltage	Power circuit: <= 1000 V AC 50/60 Hz
[Ith] conventional free air thermal current	2750 A (at 40 °C) for power circuit
Irms rated making capacity	18000 A at 1000 V AC for power circuit conforming to IEC 60158-1 18000 A at 1000 V AC for power circuit conforming to IEC 60947-4

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Rated breaking capacity	11000 A at 660...690 V for power circuit conforming to IEC 60158-1 11000 A at 660...690 V for power circuit conforming to IEC 60947-4 15000 A at 500 V for power circuit conforming to IEC 60158-1 15000 A at 500 V for power circuit conforming to IEC 60947-4 18000 A at 440 V for power circuit conforming to IEC 60158-1 18000 A at 440 V for power circuit conforming to IEC 60947-4 6000 A at 1000 V for power circuit conforming to IEC 60158-1 6000 A at 1000 V for power circuit conforming to IEC 60947-4
Associated fuse rating	2000 A aM at <= 440 V for power circuit 2400 A gI at <= 440 V for power circuit
Average impedance	0.09 mOhm - Ith 2750 A 50 Hz for power circuit
Power dissipation per pole	680 W AC-1 - Ith 2750 A
Inrush power in VA	620 VA
Hold-in power consumption in VA	10 VA 50/60 Hz
Operating time	100...150 ms closing 50...100 ms opening
Mechanical durability	1200000 cycles
Maximum operating rate	120 cyc/h 55 °C
Height	495 mm
Width	475 mm
Depth	475 mm
Net weight	52 kg

Environment

Standards	IEC 60947-4 NF C 63-110 IEC 60158-1 BS 5424 VDE 0660
Product certifications	RINA BV CSA
Protective treatment	TC TH
Ambient air temperature for operation	-5...55 °C
Ambient air temperature for storage	-60...80 °C
Operating altitude	3000 m without derating



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Longer

Lifetime extension	
Repair	No