

Product data sheet

Specifications



shunt trip release SHT - 100..240 V AC, 100..240 V DC - for EZC400

EZ4SHT200ACDC

⚠ Discontinued on: Dec 29, 2022

⚠ Discontinued

Main

Range	EasyPact
Range of product	EZC400
Device short name	SHT
Product or component type	Voltage release
Device application	Control
Voltage release type	Shunt trip release
[Uc] control circuit voltage	100...240 V AC 50/60 Hz 100...240 V DC
Circuit breaker mounting mode	Internal mounting
Range compatibility	EasyPact EasyPact EZC

Complementary

Operating threshold	0.7 Un opening
Control signal type	Maintained Impulse
Impulse duration	>= 20 ms
Supply inrush power	30 VA 35 W
Auxiliary connection terminal	Pre-wired 0...1.5 mm ²

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.5 cm
Package 1 Width	7.0 cm
Package 1 Length	9.0 cm
Package 1 Weight	80.0 g
Unit Type of Package 2	S02
Number of Units in Package 2	30
Package 2 Height	15.0 cm
Package 2 Width	30.0 cm
Package 2 Length	40.0 cm

List Price displayed is VAT EXCLUSIVE.

Package 2 Weight	5.287 kg
Unit Type of Package 3	S03
Number of Units in Package 3	60
Package 3 Height	30.0 cm
Package 3 Width	30.0 cm
Package 3 Length	40.0 cm
Package 3 Weight	5.287 kg



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better



Materials and Substances

EU RoHS Directive

[Compliant By Exemption](#)

Use Longer



Lifetime extension

Repair

No