

# Product datasheet

Specifications



## DCM Modbus SL Communication and Control Module

LV434311

### Main

Range of product	ComPact NSX100...250 ComPact NSX400...630
Device short name	breaker status control module
Product or component type	Communication module
Range compatibility	ComPact ComPact NSX

### Complementary

Communication network type	Modbus, Modbus Serial line slave4.8, 9.6, 19.2, 38.4 kbit/s on RS485
Input voltage	24 V DC
Output voltage	24 V DC
Output current	0...450 mA
Current consumption	< 30 mA 24 V DC room temperature
Power consumption in W	0.72 W
Connections - terminals	Screw type terminals
Height	34.33 mm
Width	27.4 mm
Depth	30.15 mm
Product weight	15.4 g

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.25 cm
Package 1 Width	5.9 cm
Package 1 Length	8.1 cm
Package 1 Weight	29.3 g
Unit Type of Package 2	S02
Number of Units in Package 2	66
Package 2 Height	15 cm
Package 2 Width	30 cm
Package 2 Length	40 cm
Package 2 Weight	2.449 kg

# Contractual warranty

---

Warranty (in months)

18



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



### Environmental footprint

[Environmental Disclosure](#)

[Product Environmental Profile](#)

## Use Better



### Materials and Packaging

Packaging made with recycled cardboard

Yes

Packaging without single use plastic

Yes

EU RoHS Directive

[Compliant By Exemption](#)

REACH Regulation

[Reference contains Substances of Very High Concern above the threshold](#)

## Use Longer



### Lifetime extension

Repair

No

## Use Again



### Repack and remanufacture

End of life manual availability

[End of Life Information](#)

Take-back

No