

Product data sheet

Specifications



Circuit breaker, ComPact NSX250HB1, 75kA/690VAC, MA trip unit 220A, 3 poles 3d

LV433503

⚠ Discontinued on: Nov 20, 2023

⚠ Discontinued

Product availability: Non-Stock - Not normally stocked in distribution facility
Important message: This product has been switched to new ComPacT range and is no longer commercialized.

Main

Range	ComPact
Product name	ComPact NSX
Range of Product	ComPact NSX100...250
Device short name	NSX250HB1
Product or Component Type	Circuit breaker
Device Application	Motor
Number of poles	3P
Protected poles description	3t
Line Rated Current	220 A 149 °F (65 °C)
[Ue] rated operational voltage	690 V AC 50/60 Hz
Network type	AC
Network Frequency	50/60 Hz
Suitability for isolation	Yes EN/IEC 60947-2
Utilisation category	Category A
[Icu] rated ultimate short-circuit breaking capacity	85 kA Icu 500 V AC 50/60 Hz IEC 60947-2 80 kA Icu 525 V AC 50/60 Hz IEC 60947-2 75 kA Icu 660/690 V AC 50/60 Hz IEC 60947-2
Performance level	HB1 75 kA 690 V AC
Trip unit name	MA
Trip unit technology	Magnetic
Trip unit protection functions	I
Control Type	Toggle
Circuit breaker mounting mode	Fixed

Complementary

[Ui] rated insulation voltage	800 V AC 50/60 Hz
[Uimp] rated impulse withstand voltage	8 kV
[Ics] rated service short-circuit breaking capacity	85 kA 500 V AC 50/60 Hz IEC 60947-2 80 kA 525 V AC 50/60 Hz IEC 60947-2 75 kA 660/690 V AC 50/60 Hz IEC 60947-2

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Mechanical durability	20000 cycles
Electrical durability	5000 cycles 690 V In 10000 cycles 690 V In/2 10000 cycles 440 V In 20000 cycles 440 V In/2
Mounting Support	Backplate
Upside connection	Front
Downside connection	Front
Connection pitch	1.4 in (35 mm)
Protection type	I : for short-circuit protection (magnetic)
Trip unit rating	220 A 149 °F (65 °C)
Short-time protection pick-up adjustment type Isd	Adjustable
[Isd] Short-time protection pick-up adjustment range	9...14 x In
Earth-leakage protection	Without
Number of slots for electrical auxiliaries	5
Width (W)	4.1 in (105 mm)
Height (H)	6.3 in (161 mm)
Depth (D)	3.4 in (86 mm)
Product Weight	5.3 lb(US) (2.4 kg)

Environment

Standards	EN/IEC 60947
Product Certifications	EAC CCC Marine
Overvoltage category	Class II
Electrical shock protection class	Class II
Pollution degree	3 IEC 60664-1
IP degree of protection	IP40 conforming to IEC 60529
IK degree of protection	IK07 conforming to IEC 62262
Ambient air temperature for operation	-13...158 °F (-25...70 °C)
Ambient Air Temperature for Storage	-58...185 °F (-50...85 °C)
Relative humidity	0...95 %
Operating altitude	0...6561.68 ft (0...2000 m) without derating 2000 m...5000 m with derating

Ordering and shipping details

Category	US10DE201101
Discount Schedule	0DE2
GTIN	3606480480089
Returnability	No

Packing Units

Unit Type of Package 1	PCE
------------------------	-----

Nbr. of units in pkg.	1
Package 1 Height	5.5 in (14.0 cm)
Package 1 Width	4.4 in (11.2 cm)
Package 1 Length	7.5 in (19.0 cm)
Package weight(Lbs)	4.317 lb(US) (1.958 kg)
Unit Type of Package 2	S03
Number of Units in Package 2	4
Package 2 Height	11.8 in (30.0 cm)
Package 2 Width	11.8 in (30.0 cm)
Package 2 Length	15.7 in (40.0 cm)
Package 2 Weight	18.19 lb(US) (8.25 kg)

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	593 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	10 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0.4 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0.2 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	582 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	0.3 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile

Use Better



Materials and Substances

SCIP Number	3874e08b-fcb8-4aa9-87c4-d36abebf2833
EU RoHS Directive	Compliant By Exemption
California proposition 65	WARNING: This product can expose you to chemicals including: DINP, which is known to the State of California to cause cancer, and DIDP, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Circularity Profile	End of Life Information
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.