

Product datasheet

Specifications



Circuit breaker frame, MasterPact MTZ2 08H1b fixed for MicroLogic X, 800A, 85kA/440VAC (Icu), 3P

LV864950

Main

| | |
|--------------------------------|----------------------------------|
| Range | MasterPacT |
| Product name | MasterPact MTZ2 |
| Device short name | MTZ2 08 H1b |
| Product or component type | Circuit breaker |
| Device application | Power distribution protection |
| Poles description | 3P |
| Control type | Without control unit |
| [In] rated current | 800 A at 40 °C |
| Breaking capacity code | H1b 85 kA 415 V AC |
| [Ue] rated operational voltage | 690 V AC 50/60 Hz |
| Suitability for isolation | Yes conforming to EN/IEC 60947-2 |
| Selectivity category | Category B |
| Control type | Push-button |
| Mounting mode | Fixed |

Complementary

| | |
|--|--|
| Breaking capacity | 85 kA at 690 V AC 50/60 Hz 85 kA at 380/415 V AC 50/60 Hz |
| [Ics] rated service breaking capacity | 85 kA at 690 V AC 50/60 Hz 85 kA at 380/415 V AC 50/60 Hz |
| [Icw] rated short-time withstand current | 50 kA 3 s 85 kA 1 s |
| [Icm] rated short-circuit making capacity | 187 kA 525 V AC at 50/60 Hz 187 kA 690 V AC at 50/60 Hz |
| Integrated instantaneous protection (DIN in kA peak) | 171...209 kA |
| Sensor rating | 400 A 630 A 800 A |
| [Ui] rated insulation voltage | 1000 V AC 50/60 Hz |
| [Uimp] rated impulse withstand voltage | 12 kV |
| Power dissipation in W | 42 W |
| Maximum breaking time | 25 ms |
| Maximum closing response time | 70 ms |
| Mounting support | Rails Base plate |

| | |
|-------------------------------|--|
| Upside connection | Front Rear |
| Downside connection | Front Rear |
| Connection pitch | 115 mm |
| Mechanical durability | 25000 cycles with periodic preventive maintenance |
| Electrical durability | 10000 cycles 440 V AC 50/60 Hz without maintenance conforming to EN/IEC 60947-2 10000 cycles 690 V AC 50/60 Hz without maintenance conforming to EN/IEC 60947-2 |
| Height | 352 mm |
| Width | 422 mm |
| Depth | 300 mm |
| Product weight | 50 kg |
| Standards | IEC 60947-2 |
| Product certifications | ASEFA |

Environment

| | |
|--|--|
| IP degree of protection | IP30 conforming to EN 60529 |
| Pollution degree | 3 conforming to IEC 60947-1 |
| Ambient air temperature for operation | -25...70 °C |
| Ambient air temperature for storage | -40...85 °C |
| Operating altitude | 0...2000 m without derating 2000...5000 m with derating |

Packing Units

| | |
|-------------------------------------|---------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 10.0 cm |
| Package 1 Width | 10.0 cm |
| Package 1 Length | 10.0 cm |
| Package 1 Weight | 1.0 kg |

Contractual warranty

| | |
|-----------------------------|----|
| Warranty (in months) | 18 |
|-----------------------------|----|



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

| | |
|--|---|
| Total lifecycle Carbon footprint | 687 kg CO2 eq. |
| Carbon footprint of the manufacturing phase [A1 to A3] | 314 kg CO2 eq. |
| Carbon footprint of the distribution phase [A4] | 7 kg CO2 eq. |
| Carbon footprint of the installation phase [A5] | 8 kg CO2 eq. |
| Carbon footprint of the use phase [B2, B3, B4, B6] | 255 kg CO2 eq. |
| Carbon footprint of the end-of-life phase [C1 to C4] | 103 kg CO2 eq. |
| Environmental Disclosure | Product Environmental Profile |

Use Better



Materials and Substances

| | |
|--|---|
| Packaging made with recycled cardboard | Yes |
| Packaging without single use plastic | No, we have minimized the use of plastic in the packaging in compliance with regulations and considering quality and safety standards |
| SCIP Number | F31d8a4d-e9cb-4afc-bf2c-5965742ce772 |
| EU RoHS Directive | Compliant By Exemption |
| REACH Regulation | Reference contains Substances of Very High Concern above the threshold |
| Halogen-free status | Product contains halogen above thresholds |
| PVC free | Yes |
| Silicone-free | No |

Use Longer



Lifetime extension

| | |
|--------|----|
| Repair | No |
|--------|----|

Use Again



Repack and remanufacture

| | |
|---------------------------------|---|
| Recyclability potential, in % | 71 |
| End of life manual availability | End of Life Information |
| Take-back | No |
| WEEE Label |  The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |

