

Product datasheet

Specifications



voltage release - MN - 380..415 V AC 50 Hz

21130

⚠ To be discontinued on: 15 Aug 2026

⚠ Discontinued

Main

range of product	Acti9
Product or component type	Undervoltage release
Device short name	MN
[In] rated current	AC-15 2.2 A at 415 V, AC 50/60 Hz
[Uc] control circuit voltage	380...415 V AC 50/60 Hz
Control type	Standard
9 mm pitches	2

Complementary

Range compatibility	Acti9 P25M
[Ui] rated insulation voltage	690 V AC 50/60 Hz conforming to EN/IEC 60947-2
[Uimp] rated impulse withstand voltage	6 kV conforming to EN/IEC 60947-2
Local signalling	Action indicator
Mounting mode	Fixed
Mounting support	35 mm symmetrical DIN rail
Height	92 mm
Width	18 mm
Depth	82 mm
Product weight	0.114 kg
Connections - terminals	Clamp terminal - 1 cable(s) 1...2.5 mm ² - rigid Clamp terminal - 1 cable(s) 0.75...2.5 mm ² - flexible Clamp terminal - 1 cable(s) 0.75...1.5 mm ² - flexible with ferrule Clamp terminal - 2 cable(s) 1...2.5 mm ² - rigid Clamp terminal - 2 cable(s) 0.75...2.5 mm ² - flexible Clamp terminal - 2 cable(s) 0.75...1.5 mm ² - flexible with ferrule
Tightening torque	1.4 N.m

Environment

Standards	EN/IEC 60947-2
Product certifications	CEBEC DEMKO FIMKO SEMKO NEMKO
Tropicalisation	2 conforming to EN/IEC 60947-2

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Relative humidity	95 % at 55 °C
Ambient air temperature for operation	-20...60 °C
Ambient air temperature for storage	-40...80 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.7 cm
Package 1 Width	8.2 cm
Package 1 Length	9.2 cm
Package 1 Weight	114.0 g
Unit Type of Package 2	S03
Number of Units in Package 2	30
Package 2 Height	30.0 cm
Package 2 Width	30.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	3.907 kg

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	2 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	0.8 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	0.5 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	0.2 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile

Use Better



Materials and Substances

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
SCIP Number	9da5f8d9-d60f-424a-bb30-a856a097686c
EU RoHS Directive	Compliant By Exemption
REACH Regulation	Reference contains Substances of Very High Concern above the threshold

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Recyclability potential, in %	29
End of life manual availability	No need of specific recycling operations
Take-back	No
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins