

Product datasheet

Specifications



Modbus Plus communication card - 1 Mbps

VW3A3E302

Main

Product or component type	Communication card
Range compatibility	Altivar 71 Plus Altivar 61 Plus
Communication port protocol	Modbus Plus
Connector type	9-way female SUB-D connector
Transmission rate	1 Mbps

Complementary

Number of addresses	1...64
Communication service	Messaging for Modbus CiA 402 profile I/O profile Global data : 8 I/O data Peer cop : 8 Communication monitoring can be inhibited, adjustable
Display type	1 LED for MB+ (status) Graphic display terminal for control word received Graphic display terminal for I/O data Graphic display terminal for reference received
Net weight	0.3 kg

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7.0 cm
Package 1 Width	17.0 cm
Package 1 Length	23.0 cm
Package 1 Weight	310.0 g

Contractual warranty

Warranty (in months)	18
----------------------	----

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Longer

Lifetime extension	
Repair	No