

CAL16-11B



Products Low Voltage Products and Systems Control Products Contactors Block Contactors Accessories

Parts & Services Low Voltage Products and Systems Control Products Arc Guard Systems Service Spares and Consumables

General Information

Extended Product Type:	CAL16-11B
Product ID:	SK829002-B
EAN:	7320500050422
Catalog Description:	CAL16-11B Auxiliary Contact Block
Long Description:	2 pole screw type right side mounted auxilliary contact block, instantaneous N.O. and N.C. contacts, suitable for standard industrial environments

Additional Information

ABB Industrial IT Suite:	Control IT
Battery Information:	Type NONE
Connecting terminals (delivered in open position):	M 3.5 (+,-) pozidriv 2 screw with cable clamp
Conventional Free-air Thermal Current (I_{th}):	acc. to IEC 60947-5-1, q = 40 °C 16 A
Country of Origin:	India (IN)
Customs Tariff Number:	85369001
Data Sheet, Technical Information:	1SBC100122C0202
Declaration of Conformity - CE:	1SFA1-46
Degree of Protection:	acc. to IEC 60529, IEC 60947-1, EN 60529 Coil Terminals IP20
EAN:	7320500050422
ETIM 4:	EC000041 - Auxiliary contact block
ETIM 5:	EC000041 - Auxiliary contact block
ETIM 6:	EC000041 - Auxiliary contact block
Industrial IT Certification Level:	0
Instructions and Manuals:	5309660-30
Invoice Description:	CAL16-11B Auxiliary Contact Block
Made To Order:	No
Minimum Order Quantity:	1 piece
Minimum Switching Capacity:	0.25 VA/ 12 V / 5 mA
Object Classification Code:	K
Package Level 1 Gross Weight:	0.060 kg
Package Level 1 Height:	18 mm
Package Level 1 Length:	100 mm
Package Level 1 Units:	1 piece
Package Level 1 Width:	100 mm
Part Type:	New
Power Loss:	at Rated Operating Conditions per Pole 0.2 W
Product Main Type:	CAL16
Product Name:	Auxiliary Contact Block
Product Net Depth:	70 mm
Product Net Height:	68 mm
Product Net Weight:	0.05 kg
Product Net Width:	12.5 mm
Quote Only:	No

Rated Breaking Capacity acc. to IEC 60947-5-1:	10 x Ie AC-15
Rated Frequency (f):	Supply Circuit 50 Hz Supply Circuit 60 Hz
Rated Insulation Voltage (Ui):	acc. to IEC 60947-5-1 and VDE 0110 (Gr. C) 690 V
Rated Making Capacity acc. to IEC 60947-5-1:	10 x Ie AC-15
Rated Operational Current AC-15 (Ie):	(500 V) 1 A (24 / 127 V) 6 A (690 V) 1 A (380 / 440 V) 4 A (220 / 240 V) 6 A
Rated Operational Current DC-13 (Ie):	(250 V) 0.6 A (72 V) 4 A (24 V) 6 A (125 V) 1.8 A (48 V) 6 A
Rated Short-time Withstand Current (Icw):	for 0.1 s 100 A for 1 s 50 A
Replaced Product ID (OLD):	SK829001-B
Selling Unit of Measure:	piece
Short Description:	AUX. CONTACT#CAL16-11B
Short-Circuit Protective Devices:	Auxiliary Circuit - gG Type Fuses 10 A
Stocked At (Warehouses):	Logistic Center Sweden Auburn Hills, MI
Suitable For:	A-line
Suitable for Product Class:	CONTACTORS
Technical Information:	AUXILIARY CONTACT
UNSPSC:	39121500

