

Product data sheet

Specifications



on mounting plate DOL starter - TeSys LC4-D - 12 A - coil 380 V AC

LC4D12AQ7

⚠ Discontinued on: Jul 24, 2022

⚠ Discontinued

Main

Range of product	TeSys
Device short name	LC4
Product or component type	DOL starter
Motor power kW	3 kW at 220...230 V AC 50/60 Hz 7.5 kW at 500 V AC 50/60 Hz 5.5 kW at 380...400 V AC 50/60 Hz 5.5 kW at 415 V AC 50/60 Hz 5.5 kW at 440 V AC 50/60 Hz
Utilisation category	AC-3
[Ue] rated operational voltage	380 V AC 50/60 Hz
[Ie] rated operational current	16 A

Complementary

Device composition	Fuse disconnecter Contactor
Mounting support	Plate
Width	86 mm
Height	173 mm
Depth	98 mm
Net weight	0.87 kg

Contractual warranty

Warranty (in months)	18
----------------------	----

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Longer



Lifetime extension

Repair

No