

# Product datasheet

Specifications



## power cable for military connector type 3,3mm<sup>2</sup> - w/o brake - length 5m

VW3M5123R50

⚠ Discontinued on: Mar 1, 2019 AD

⚠ End-of-service on: Dec 31, 2025 AD

⚠ Discontinued - Service only

## Main

Product or component type	Power cable
Accessory / separate part type	Pre-wired connector
Accessory / separate part category	Connection accessories

## Complementary

Product compatibility	Servo motor- BCH connector motor flange size: 180 mm (1 motor stacks), nominal speed: 2000 rpm without holding brake Servo motor- BCH connector motor flange size: 180 mm (2 motor stacks), nominal speed: 2000 rpm without holding brake Servo motor- BCH connector motor flange size: 180 mm (2 motor stacks), nominal speed: 1500 rpm without holding brake Servo motor- BCH connector motor flange size: 180 mm (3 motor stacks), nominal speed: 2000 rpm without holding brake
Accessory / separate part destination	Between servo motor and servo drive
Range compatibility	Lexium 23 Plus
Cable length	5 m
Electrical connection	1 free end with flying leads for servo drive side 1 connector, material: metal for servo motor side
Cable composition	4 x 3.3 mm <sup>2</sup>
Product weight	1.75 kg

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	24.000 cm
Package 1 Width	6.000 cm
Package 1 Length	29.000 cm
Package 1 Weight	2.061 kg

## Contractual warranty

Warranty (in months)	18
----------------------	----



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Use Longer



#### Lifetime extension

Repair

No