

Product data sheet

Specifications



servo motor BMH - 48 Nm - 4000 rpm - untapped shaft - with brake - IP65/IP67

BMH1902P26F2A

⚠ Discontinued on: 8 Jun 2017

⚠ To be end-of-service on: 31 Dec 2026

⚠ Discontinued

Main

Device short name	BMH
Product or component type	Servo motor
Maximum mechanical speed	4000 rpm
Continuous stall torque	37.4 N.m for LXM32.D72N4 at 24 A, 400 V, three phase 37.4 N.m for LXM32.D72N4 at 24 A, 480 V, three phase 48 N.m for LXM32MD85N4 at 32 A, 400 V, three phase 48 N.m for LXM32MD85N4 at 32 A, 480 V, three phase 48 N.m for LXM32MC10N4 at 40 A, 400 V, three phase 48 N.m for LXM32MC10N4 at 40 A, 480 V, three phase
Peak stall torque	101 N.m for LXM32.D72N4 at 24 A, 400 V, three phase 101 N.m for LXM32.D72N4 at 24 A, 480 V, three phase 115.5 N.m for LXM32MD85N4 at 32 A, 400 V, three phase 115.5 N.m for LXM32MD85N4 at 32 A, 480 V, three phase 130.7 N.m for LXM32MC10N4 at 40 A, 400 V, three phase 130.7 N.m for LXM32MC10N4 at 40 A, 480 V, three phase
Nominal output power	5900 W for LXM32.D72N4 at 24 A, 400 V, three phase 5900 W for LXM32.D72N4 at 24 A, 480 V, three phase 6070 W for LXM32MD85N4 at 32 A, 400 V, three phase 6070 W for LXM32MD85N4 at 32 A, 480 V, three phase 6070 W for LXM32MC10N4 at 40 A, 400 V, three phase 6070 W for LXM32MC10N4 at 40 A, 480 V, three phase
Nominal torque	22.3 N.m for LXM32.D72N4 at 24 A, 400 V, three phase 22.3 N.m for LXM32.D72N4 at 24 A, 480 V, three phase 29 N.m for LXM32MD85N4 at 32 A, 400 V, three phase 29 N.m for LXM32MD85N4 at 32 A, 480 V, three phase 29 N.m for LXM32MC10N4 at 40 A, 400 V, three phase 29 N.m for LXM32MC10N4 at 40 A, 480 V, three phase
Nominal speed	2000 rpm for LXM32MC10N4 at 40 A, 400 V, three phase 2000 rpm for LXM32MC10N4 at 40 A, 480 V, three phase 2500 rpm for LXM32.D72N4 at 24 A, 400 V, three phase 2500 rpm for LXM32.D72N4 at 24 A, 480 V, three phase 2000 rpm for LXM32MD85N4 at 32 A, 400 V, three phase 2000 rpm for LXM32MD85N4 at 32 A, 480 V, three phase
Product compatibility	LXM32.D72N4 at 400...480 V three phase
Shaft end	Smooth shaft
IP degree of protection	IP65 standard IP67 with IP67 kit
Speed feedback resolution	32768 points/turn
Holding brake	With
Mounting support	International standard flange
Electrical connection	Rotatable right-angled connectors

Complementary

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Range compatibility	Lexium 32
[Us] rated supply voltage	480 V
Network number of phases	Three phase
Continuous stall current	30.8 A
Continuous power	6.1 W
Maximum current Irms	72 A for LXM32.D72N4
Maximum permanent current	114 A
Second shaft	Without second shaft end
Shaft diameter	38 mm
Shaft length	80 mm
Feedback type	Single turn SinCos Hiperface
Holding torque	80 N.m holding brake
Motor flange size	190 mm
Number of motor stacks	2
Torque constant	1.56 N.m/A at 120 °C
Back emf constant	108.3 V/krpm at 120 °C
Number of motor poles	10
Rotor inertia	144.8 kg.cm²
Stator resistance	0.15 Ohm at 20 °C
Stator inductance	3.86 mH at 20 °C
Stator electrical time constant	25.7 ms at 20 °C
Maximum radial force Fr	4200 N at 1000 rpm
Maximum axial force Fa	0.2 x Fr
Brake pull-in power	40 W
Type of cooling	Natural convection
Length	310 mm
Centring collar diameter	180 mm
Centring collar depth	4 mm
Number of mounting holes	4
Mounting holes diameter	14 mm
Circle diameter of the mounting holes	215 mm
Product weight	32.5 kg
Sizing reference	BMH1902P
Network number of phases	3
Accuracy error [angular]	4.8 °
Temperature copper hot	135 °C
Temperature magnet hot	100 °C
Temperature magnet rt	20 °C

Packing Units

Unit Type of Package 1	PCE
------------------------	-----

Number of Units in Package 1	1
Package 1 Height	30.0 cm
Package 1 Width	40.0 cm
Package 1 Length	79.5 cm
Package 1 Weight	31.5 kg

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

Materials and Substances	
SCIP Number	A7df881f-135f-4256-b8c2-ea55d4c9a151
EU RoHS Directive	Compliant By Exemption
REACH Regulation	Reference contains Substances of Very High Concern above the threshold
PVC free	Yes

Use Longer

Lifetime extension	
Repair	No

Use Again

Repack and remanufacture	
End of life manual availability	No need of specific recycling operations
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins