

Overload relay 50...200 A for motor protection Size S6, CLASS 5...30E Contactor mounting/stand-alone installation Main circuit: busbar connection Auxiliary circuit: Screw terminal Manual-Automatic-Reset Internal ground fault detection



|  |   |
|--|---|
| product brand name   | SIRIUS  |
| product designation  | solid-state overload relay  |
| product type designation   | 3RB2  |
| <b>General technical data</b>  |   |
| size of overload relay   | S6  |
| size of contactor can be combined company-specific   | S6  |
| type of calculation of power loss current-dependent  | quadratic   |
| insulation voltage with degree of pollution 3 at AC rated value  | 1 000 V   |
| surge voltage resistance rated value   | 8 kV  |
| maximum permissible voltage for protective separation  |   |
| <ul style="list-style-type: none"> <li>in networks with ungrounded star point between auxiliary and auxiliary circuit</li> </ul> | 300 V   |
| <ul style="list-style-type: none"> <li>in networks with grounded star point between auxiliary and auxiliary circuit</li> </ul>   | 300 V   |
| <ul style="list-style-type: none"> <li>in networks with ungrounded star point between main and auxiliary circuit</li> </ul>      | 600 V   |
| <ul style="list-style-type: none"> <li>in networks with grounded star point between main and auxiliary circuit</li> </ul>        | 690 V   |
| shock resistance   | 15 g / 11 ms  |
| <ul style="list-style-type: none"> <li>according to IEC 60068-2-27</li> </ul>  | 15 g / 11 ms  |
| vibration resistance   | 1 ... 6 Hz, 15 mm; 6 ... 500 Hz, 20 m/s <sup>2</sup> ; 10 cycles  |
| thermal current  | 200 A   |
| recovery time after overload trip  |   |
| <ul style="list-style-type: none"> <li>with automatic reset typical</li> </ul>   | 3 min   |
| <ul style="list-style-type: none"> <li>with remote-reset</li> </ul>  | 0 min   |
| <ul style="list-style-type: none"> <li>with manual reset</li> </ul>  | 0 min   |
| reference code according to IEC 81346-2  | F   |
| Substance Prohibitance (day/month/year)  | 07/01/2006  |
| SVHC substance name  | Lead CAS-No. 7439-92-1<br>Lead monoxide (lead oxide) CAS-No. 1317-36-8<br>6,6'-di-tert-butyl-2,2'-methylenedi-p-cresol CAS-No. 119-47-1 |
| Net Weight   | 1.045 kg  |
| <b>Ambient conditions</b>  |   |
| installation altitude at height above sea level maximum  | 2 000 m   |
| ambient temperature  |   |
| <ul style="list-style-type: none"> <li>during operation</li> </ul>   | -25 ... +60 °C  |
| <ul style="list-style-type: none"> <li>during storage</li> </ul>   | -40 ... +80 °C  |
| <ul style="list-style-type: none"> <li>during transport</li> </ul>   | -40 ... +80 °C  |
| temperature compensation   | -25 ... +60 °C  |
| relative humidity during operation   | 10 ... 95 %   |
| <b>Main circuit</b>  |   |

|  |  |
|--|--|
| <b>number of poles for main current circuit</b>  | 3  |
| <b>adjustable current response value current of the current-dependent overload release</b> | 50 ... 200 A   |
| <b>operating voltage</b>   |  |
| • rated value  | 1 000 V  |
| • for remote-reset function at DC  | 24 V   |
| • at AC-3e rated value maximum   | 1 000 V  |
| <b>operating frequency rated value</b>   | 50 ... 60 Hz   |
| <b>operational current rated value</b>   | 200 A  |
| operational current at AC-3e at 400 V rated value  | 200 A  |
| <b>operating power</b>   |  |
| • for 3-phase motors at 400 V at 50 Hz   | 30 ... 90 kW   |
| • for AC motors at 500 V at 50 Hz  | 30 ... 132 kW  |
| • for AC motors at 690 V at 50 Hz  | 55 ... 160 kW  |
| <b>Auxiliary circuit</b>   |  |
| <b>design of the auxiliary switch</b>  | integrated   |
| <b>number of NC contacts for auxiliary contacts</b>  | 1  |
| • note   | for contactor disconnection                            |
| <b>number of NO contacts for auxiliary contacts</b>  | 1  |
| • note   | for message "tripped"                                  |
| number of CO contacts for auxiliary contacts   | 0  |
| <b>operational current of auxiliary contacts at AC-15</b>                                  |  |
| • at 24 V  | 4 A  |
| • at 110 V   | 4 A  |
| • at 120 V   | 4 A  |
| • at 125 V   | 4 A  |
| • at 230 V   | 3 A  |
| <b>operational current of auxiliary contacts at DC-13</b>                                  |  |
| • at 24 V  | 2 A  |
| • at 60 V  | 0.55 A   |
| • at 110 V   | 0.3 A  |
| • at 125 V   | 0.3 A  |
| • at 220 V   | 0.11 A   |
| <b>Protective and monitoring functions</b>   |  |
| <b>trip class</b>  | CLASS 5E, 10E, 20E and 30E adjustable                  |
| <b>design of the overload release</b>  | electronic   |
| response value current of the grounding protection minimum                                 | 0.75 x I <sub>Motor</sub>                              |
| <b>response time of the grounding protection in settled state</b>                          | 1 000 ms   |
| <b>operating range of the grounding protection relating to current set value</b>           |  |
| • minimum  | I <sub>Motor</sub> > lower current setting value       |
| • maximum  | I <sub>Motor</sub> < upper current setting value x 3.5 |
| <b>UL/CSA ratings</b>  |  |
| <b>full-load current (FLA) for 3-phase AC motor</b>  |  |
| • at 480 V rated value   | 200 A  |
| • at 600 V rated value   | 200 A  |
| <b>contact rating of auxiliary contacts according to UL</b>                                | B600 / R300  |
| <b>Short-circuit protection</b>  |  |
| <b>design of the fuse link</b>   |  |
| • for short-circuit protection of the main circuit   |  |
| — with type of coordination 1 required   | gG: 355 A, Class L: 601 A                              |
| — with type of coordination 2 required   | gG: 315 A  |
| • for short-circuit protection of the auxiliary switch required                            | fuse gG: 6 A   |
| <b>Installation/ mounting/ dimensions</b>  |  |
| <b>mounting position</b>   | any  |
| <b>fastening method</b>  | Contacteur mounting/stand-alone installation           |
| <b>height</b>  | 119 mm   |
| <b>width</b>   | 120 mm   |
| <b>depth</b>   | 155 mm   |

|  |  |
|--|--|
| <b>required spacing</b>  |  |
| <ul style="list-style-type: none"> <li>● for grounded parts <ul style="list-style-type: none"> <li>— forwards 0 mm</li> <li>— backwards 0 mm</li> <li>— upwards 0 mm</li> <li>— at the side 6 mm</li> <li>— downwards 0 mm</li> </ul> </li> <li>● for live parts <ul style="list-style-type: none"> <li>— forwards 0 mm</li> <li>— backwards 0 mm</li> <li>— upwards 0 mm</li> <li>— downwards 0 mm</li> <li>— at the side 6 mm</li> </ul> </li> </ul> |  |

**Connections/ Terminals**

|   |   |
|---|---|
| <b>product component removable terminal for auxiliary and control circuit</b> | Yes   |
| <b>type of electrical connection</b>  | busbar connection<br>screw-type terminals   |
| <b>arrangement of electrical connectors for main current circuit</b>          | Top and bottom  |
| <b>type of connectable conductor cross-sections</b>                           | <ul style="list-style-type: none"> <li>● for auxiliary contacts <ul style="list-style-type: none"> <li>— solid 1x (0.5 ... 4 mm<sup>2</sup>), 2x (0.5 ... 2.5 mm<sup>2</sup>)</li> <li>— solid or stranded 1x (0,5 ... 4 mm<sup>2</sup>), 2x (0,5 ... 2,5 mm<sup>2</sup>)</li> <li>— finely stranded with core end processing 1x (0.5 ... 2.5 mm<sup>2</sup>), 2x (0.5 ... 1.5 mm<sup>2</sup>)</li> </ul> </li> <li>● for AWG cables for auxiliary contacts 2x (20 ... 14)</li> </ul> |
| <b>tightening torque</b>  | <ul style="list-style-type: none"> <li>● for main contacts with screw-type terminals 10 ... 12 N·m</li> <li>● for auxiliary contacts with screw-type terminals 0.8 ... 1.2 N·m</li> </ul>   |
| <b>design of the thread of the connection screw</b>                           | <ul style="list-style-type: none"> <li>● for main contacts M10</li> <li>● of the auxiliary and control contacts M3</li> </ul>   |

**Electrical Safety**

|  |  |
|--|--|
| <b>protection class IP on the front according to IEC 60529</b> | IP00; IP20 with box terminal/cover                                       |
| <b>touch protection on the front according to IEC 60529</b>    | finger-safe, for vertical contact from the front with box terminal/cover |

**Communication/ Protocol**

|  |    |
|--|----|
| <b>type of voltage supply via input/output link master</b> | No |
|--|----|

**Electromagnetic compatibility**

|  |  |
|--|--|
| <b>conducted interference</b>                              | <ul style="list-style-type: none"> <li>● due to burst according to IEC 61000-4-4 2 kV (power ports), 1 kV (signal ports) corresponds to degree of severity 3</li> <li>● due to conductor-earth surge according to IEC 61000-4-5 2 kV (line to earth) corresponds to degree of severity 3</li> <li>● due to conductor-conductor surge according to IEC 61000-4-5 1 kV (line to line) corresponds to degree of severity 3</li> <li>● due to high-frequency radiation according to IEC 61000-4-6 10 V in frequency range 0.15 to 80 MHz, modulation 80 % AM with 1 kHz</li> </ul> |
| <b>field-based interference according to IEC 61000-4-3</b> | 10 V/m   |
| <b>electrostatic discharge according to IEC 61000-4-2</b>  | 6 kV contact discharge / 8 kV air discharge  |

**Display**

|                                      |              |
|--------------------------------------|--------------|
| display version for switching status | Slide switch |
|--------------------------------------|--------------|

**Approvals Certificates**

|                    |                          |
|--------------------|--------------------------|
| <b>Environment</b> | General Product Approval |
|--------------------|--------------------------|

[Environmental Confirmations](#)



|     |                                |                   |                      |
|-----|--------------------------------|-------------------|----------------------|
| EMV | For use in hazardous locations | Test Certificates | Maritime application |
|-----|--------------------------------|-------------------|----------------------|



[Special Test Certificate](#)

[Type Test Certificates/Test Report](#)



Maritime application

other



[Confirmation](#)

[Confirmation](#)



other

[Miscellaneous](#)

Further information

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information for data generation and storage

<https://support.industry.siemens.com/cs/ww/en/view/109995012>

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RB2153-4FC2>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RB2153-4FC2>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

[https://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3RB2153-4FC2&lang=en](https://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RB2153-4FC2&lang=en)

Cax online generator

<https://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RB2153-4FC2>

Characteristic curves

[https://curves.simaris.siemens.com/curves/<mmp\\_prod\\_noCOMP="HAUPT"></mmp\\_prod\\_no>](https://curves.simaris.siemens.com/curves/<mmp_prod_noCOMP=)



