



Figure similar

Article No. : 1FK7042-2AK71-1PA0

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Engineering data	
Rated speed (100 K)	6,000 rpm
Number of poles	8
Rated torque (100 K)	1.5 Nm
Rated current	2.5 A
Static torque (60 K)	2.50 Nm
Static torque (100 K)	3.00 Nm
Stall current (60 K)	3.55 A
Stall current (100 K)	4.40 A
Moment of inertia	2.900 kgcm²
Efficiency	89.0 %

Physical constants	
Torque constant	0.68 Nm/A
Voltage constant at 20° C	44.5 V/1000*min ⁻¹
Winding resistance at 20° C	1.15 Ω
Rotating field inductance	8.6 mH
Electrical time constant	7.50 ms
Mechanical time constant	2.15 ms
Thermal time constant	30 min
Shaft torsional stiffness	15,500 Nm/rad
Net weight of the motor	4.6 kg

Mechanical data	
Motor type	Permanent-magnet synchronous motor
Motor type	Compact
Shaft height	48
Cooling	Natural cooling
Radial runout tolerance	0.040 mm
Concentricity tolerance	0.08 mm
Axial runout tolerance	0.08 mm
Vibration severity grade	Grade A
Connector size	1
Degree of protection	IP64
Design acc. to Code I	IM B5 (IM V1, IM V3)
Temperature monitoring	Pt1000 temperature sensor
Electrical connectors	Connectors for signals and power rotatable
Color of the housing	Standard (Anthracite RAL 7016)
Holding brake	without holding brake
Shaft end	Feather key
Encoder system	Resolver R14DQ: resolver 14 bits (resolution 16384, internal 2-pole)

Optimum operating point	
Optimum speed	5,000 rpm
Optimum power	1.0 kW

Limiting data	
Max. permissible speed (mech.)	9,000 rpm
Max. permissible speed (inverter)	9,000 rpm
Maximum torque	10.5 Nm
Maximum current	15.3 A

Recommended Motor Module	
Rated inverter current	5 A
Maximum inverter current	15 A
Maximum torque	10.30 Nm