



SIPLUS S7-1500 F-DI 16x24 V DC based on 6ES7526-1BH00-0AB0 with conformal coating, -30...+60 °C, F digital input module, 35 mm overall width; up to PL E (ISO13849-1)/ SIL 3 (IEC 61508)

| General information | |
|--|---|
| Product type designation | F-DI 16x24VDC |
| Firmware version | |
| • FW update possible | Yes |
| based on | 6ES7526-1BH00-0AB0 |
| Product function | |
| • I&M data | Yes; I&M0 to I&M3 |
| Engineering with | |
| • STEP 7 TIA Portal configurable/integrated from version | see entry ID: 109746275 |
| Operating mode | |
| • DI | Yes |
| • MSI | No |
| Supply voltage | |
| Rated value (DC) | 24 V |
| permissible range, lower limit (DC) | 19.2 V |
| permissible range, upper limit (DC) | 28.8 V |
| Reverse polarity protection | Yes |
| Input current | |
| Current consumption (rated value) | 50 mA; without load |
| Current consumption, max. | 60 mA; without load |
| Encoder supply | |
| Number of outputs | 4 |
| Short-circuit protection | Yes; Electronic (response threshold 0.7 A to 1.8 A) |
| 24 V encoder supply | |
| • 24 V | Yes; min. L+ (-1.5 V) |
| • Short-circuit protection | Yes |
| • Output current, max. | 300 mA; Max. 100 mA when mounted vertically |
| Power | |
| Power consumption from the backplane bus | 0.9 W |
| Power loss | |
| Power loss, typ. | 4.6 W |
| Address area | |
| Address space per module | |
| • Inputs | 9 byte; S7-300/400F CPU, 8 byte |
| • Outputs | 5 byte; S7-300/400F CPU, 4 byte |
| Hardware configuration | |
| Automatic encoding | Yes |
| • Electronic coding element type F | Yes |

| Digital inputs | |
|---|--|
| Number of digital inputs | 16 |
| Sourcing/sinking input | Yes; P-reading |
| Input characteristic curve in accordance with IEC 61131, type 1 | Yes |
| Input voltage | |
| <ul style="list-style-type: none"> Rated value (DC) | 24 V |
| <ul style="list-style-type: none"> for signal "0" | -30 to +5 V |
| <ul style="list-style-type: none"> for signal "1" | +15 to +30 V |
| Input current | |
| <ul style="list-style-type: none"> for signal "1", typ. | 3.7 mA |
| Input delay (for rated value of input voltage) | |
| for standard inputs | |
| — parameterizable | Yes |
| — at "0" to "1", min. | 0.4 ms |
| — at "0" to "1", max. | 20 ms |
| — at "1" to "0", min. | 0.4 ms |
| — at "1" to "0", max. | 20 ms |
| Cable length | |
| <ul style="list-style-type: none"> shielded, max. | 1 000 m |
| <ul style="list-style-type: none"> unshielded, max. | 500 m |
| Interrupts/diagnostics/status information | |
| Diagnostics function | Yes |
| Alarms | |
| <ul style="list-style-type: none"> Diagnostic alarm | Yes |
| <ul style="list-style-type: none"> Hardware interrupt | No |
| Diagnoses | |
| <ul style="list-style-type: none"> Monitoring the supply voltage | Yes |
| <ul style="list-style-type: none"> Wire break | No |
| <ul style="list-style-type: none"> Short-circuit | Yes |
| <ul style="list-style-type: none"> Group error | Yes |
| Diagnostics indication LED | |
| <ul style="list-style-type: none"> RUN LED | Yes; green LED |
| <ul style="list-style-type: none"> ERROR LED | Yes; red LED |
| <ul style="list-style-type: none"> Channel status display | Yes; green LED |
| <ul style="list-style-type: none"> for channel diagnostics | Yes; red LED |
| <ul style="list-style-type: none"> for module diagnostics | Yes; red LED |
| Potential separation | |
| Potential separation channels | |
| <ul style="list-style-type: none"> between the channels and backplane bus | Yes |
| Isolation | |
| Isolation tested with | 707 V DC (type test) |
| Standards, approvals, certificates | |
| Suitable for safety functions | Yes |
| Highest safety class achievable in safety mode | |
| <ul style="list-style-type: none"> Performance level according to ISO 13849-1 | PLe |
| <ul style="list-style-type: none"> SIL acc. to IEC 61508 | SIL 3 |
| Probability of failure (for service life of 20 years and repair time of 100 hours) | |
| — Low demand mode: PFDavg in accordance with SIL3 | < 5.00E-05 |
| — High demand/continuous mode: PFH in accordance with SIL3 | < 1.00E-09 1/h |
| Ambient conditions | |
| Ambient temperature during operation | |
| <ul style="list-style-type: none"> horizontal installation, min. | -30 °C; = Tmin (incl. condensation/frost) |
| <ul style="list-style-type: none"> horizontal installation, max. | 60 °C; = Tmax |
| <ul style="list-style-type: none"> vertical installation, min. | -30 °C; = Tmin |
| <ul style="list-style-type: none"> vertical installation, max. | 40 °C; = Tmax |
| Altitude during operation relating to sea level | |
| <ul style="list-style-type: none"> Installation altitude above sea level, max. | 5 000 m; Restrictions for installation altitudes > 2 000 m, see manual |

| | | |
|---|---|-----------------------|
| Relative humidity | | |
| <ul style="list-style-type: none"> With condensation, tested in accordance with IEC 60068-2-38, max. | 100 %; RH incl. condensation/frost (no commissioning under condensation conditions) | |
| Resistance | | |
| Coolants and lubricants | | |
| — Resistant to commercially available coolants and lubricants | Yes; Incl. diesel and oil droplets in the air | |
| Use in stationary industrial systems | | |
| — to biologically active substances according to EN 60721-3-3 | Yes; Class 3B2 mold, fungus and dry rot spores (with the exception of fauna); Class 3B3 on request | |
| — to chemically active substances according to EN 60721-3-3 | Yes; Class 3C4 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); * | |
| — to mechanically active substances according to EN 60721-3-3 | Yes; Class 3S4 incl. sand, dust, * | |
| Use on ships/at sea | | |
| — to biologically active substances according to EN 60721-3-6 | Yes; Class 6B2 mold and fungal spores (excluding fauna); Class 6B3 on request | |
| — to chemically active substances according to EN 60721-3-6 | Yes; Class 6C3 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); * | |
| — to mechanically active substances according to EN 60721-3-6 | Yes; Class 6S3 incl. sand, dust; * | |
| Usage in industrial process technology | | |
| — Against chemically active substances acc. to EN 60654-4 | Yes; Class 3 (excluding trichlorethylene) | |
| — Environmental conditions for process, measuring and control systems acc. to ANSI/ISA-71.04 | Yes; Level GX group A/B (excluding trichlorethylene; harmful gas concentrations up to the limits of EN 60721-3-3 class 3C4 permissible); level LC3 (salt spray) and level LB3 (oil) | |
| Remark | | |
| — Note regarding classification of environmental conditions acc. to EN 60721, EN 60654-4 and ANSI/ISA-71.04 | * The supplied plug covers must remain in place over the unused interfaces during operation! | |
| Conformal coating | | |
| <ul style="list-style-type: none"> Coatings for printed circuit board assemblies acc. to EN 61086 Protection against fouling acc. to EN 60664-3 Military testing according to MIL-I-46058C, Amendment 7 Qualification and Performance of Electrical Insulating Compound for Printed Board Assemblies according to IPC-CC-830A | <p>Yes; Class 2 for high reliability</p> <p>Yes; Type 1 protection</p> <p>Yes; Discoloration of coating possible during service life</p> <p>Yes; Conformal coating, Class A</p> | |
| Dimensions | | |
| Width | 35 mm | |
| Height | 147 mm | |
| Depth | 129 mm | |
| Weights | | |
| Weight, approx. | 280 g | |
| Classifications | | |
| | Version | Classification |
| eClass | 14 | 27-24-22-04 |
| eClass | 12 | 27-24-22-04 |
| eClass | 9.1 | 27-24-22-04 |
| eClass | 9 | 27-24-22-04 |
| eClass | 8 | 27-24-22-04 |
| eClass | 7.1 | 27-24-22-04 |
| eClass | 6 | 27-24-22-04 |
| ETIM | 10 | EC001419 |
| ETIM | 9 | EC001419 |
| ETIM | 8 | EC001419 |
| ETIM | 7 | EC001419 |
| IDEA | 4 | 3566 |
| UNSPSC | 15 | 32-15-17-05 |
| Approvals / Certificates | | |

General Product Approval



[Manufacturer Declaration](#)



[China RoHS](#)



General Product Approval

EMV

For use in hazardous locations

[China RoHS](#)



For use in hazardous locations

Functional Safety

Maritime application



[TUEV](#)

[TUEV](#)



last modified:

10/23/2025