

# Product datasheet

Specifications



## Switch-disconnector Masterpact MTZ3 40 HA - 4000 A - 3P fixed

LV848108

### Main

|                           |                       |
|---------------------------|-----------------------|
| Range                     | MasterPact            |
| Product or component type | Switch disconnector   |
| Device application        | Distribution          |
| Switch-disconnector name  | MasterPact MTZ3 40 HA |
| Poles description         | 3P                    |
| Network type              | AC                    |
| Network frequency         | 50/60 Hz              |

### Complementary

|                                           |                                                                                                                                          |
|-------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------|
| Control type                              | Push-button                                                                                                                              |
| Mounting mode                             | Fixed                                                                                                                                    |
| [Ue] rated operational voltage            | 690 V AC 50/60 Hz conforming to EN/IEC 60947-3                                                                                           |
| [Ie] rated operational current            | 4000 A AC 50/60 Hz 690 V                                                                                                                 |
| [Ui] rated insulation voltage             | 1000 V AC 50/60 Hz conforming to EN/IEC 60947-3                                                                                          |
| [Uimp] rated impulse withstand voltage    | 12 kV conforming to EN/IEC 60947-3                                                                                                       |
| [Icw] rated short-time withstand current  | 85 kA during 1 s conforming to EN/IEC 60947-3<br>85 kA during 3 s conforming to EN/IEC 60947-3                                           |
| [Icm] rated short-circuit making capacity | 187 kA peak 220...690 V AC at 50/60 Hz                                                                                                   |
| Utilisation category                      | AC-23A<br>AC-3                                                                                                                           |
| Breaking capacity                         | 85 kA Icu at 220...690 V AC 50/60 Hz conforming to EN/IEC 60947-2                                                                        |
| [Ics] rated service breaking capacity     | 85 kA at 220...690 V AC 50/60 Hz conforming to EN/IEC 60947-2                                                                            |
| performance level                         | HA                                                                                                                                       |
| Suitability for isolation                 | Yes conforming to EN/IEC 60947-3                                                                                                         |
| Contact position indicator                | Yes                                                                                                                                      |
| Visible break                             | No                                                                                                                                       |
| Mechanical durability                     | 10000 cycles with periodic preventive maintenance conforming to EN/IEC 60947-3                                                           |
| Electrical durability                     | AC-23A: 1500 cycles 440 V AC 50/60 Hz conforming to EN/IEC 60947-3<br>AC-23A: 1500 cycles 690 V AC 50/60 Hz conforming to EN/IEC 60947-3 |
| Connection pitch                          | 230 mm                                                                                                                                   |
| Height                                    | 352 mm                                                                                                                                   |
| Width                                     | 767 mm                                                                                                                                   |
| Depth                                     | 300 mm                                                                                                                                   |

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

# Environment

|                                       |                                  |
|---------------------------------------|----------------------------------|
| Product weight                        | 120 kg                           |
| Standards                             | EN/IEC 60947-3                   |
| Product certifications                | IECEE CB Scheme                  |
| IP degree of protection               | IP30                             |
| Pollution degree                      | 3 conforming to EN/IEC 60947-4-1 |
| Ambient air temperature for operation | -25...70 °C                      |
| Ambient air temperature for storage   | -40...85 °C                      |

# Packing Units

|                              |           |
|------------------------------|-----------|
| Unit Type of Package 1       | PCE       |
| Number of Units in Package 1 | 1         |
| Package 1 Height             | 57.0 cm   |
| Package 1 Width              | 64.0 cm   |
| Package 1 Length             | 120.0 cm  |
| Package 1 Weight             | 118.43 kg |

# Contractual warranty

|                      |    |
|----------------------|----|
| Warranty (in months) | 18 |
|----------------------|----|



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



### Environmental footprint

|                                                        |                                               |
|--------------------------------------------------------|-----------------------------------------------|
| Total lifecycle Carbon footprint                       | 2 960 kg CO2 eq.                              |
| Carbon footprint of the manufacturing phase [A1 to A3] | 587 kg CO2 eq.                                |
| Carbon footprint of the distribution phase [A4]        | 13 kg CO2 eq.                                 |
| Carbon footprint of the installation phase [A5]        | 15 kg CO2 eq.                                 |
| Carbon footprint of the use phase [B2, B3, B4, B6]     | 2 153 kg CO2 eq.                              |
| Carbon footprint of the end-of-life phase [C1 to C4]   | 192 kg CO2 eq.                                |
| Environmental Disclosure                               | <a href="#">Product Environmental Profile</a> |

## Use Better



### Materials and Substances

|                                        |                                                                                                                                       |
|----------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------|
| Packaging made with recycled cardboard | Yes                                                                                                                                   |
| Packaging without single use plastic   | No, we have minimized the use of plastic in the packaging in compliance with regulations and considering quality and safety standards |
| SCIP Number                            | F31d8a4d-e9cb-4afc-bf2c-5965742ce772                                                                                                  |
| EU RoHS Directive                      | <a href="#">Compliant By Exemption</a>                                                                                                |
| REACH Regulation                       | <a href="#">Reference contains Substances of Very High Concern above the threshold</a>                                                |
| Halogen-free status                    | Product contains halogen above thresholds                                                                                             |
| PVC free                               | Yes                                                                                                                                   |
| Silicone-free                          | No                                                                                                                                    |

## Use Longer



### Lifetime extension

|        |    |
|--------|----|
| Repair | No |
|--------|----|

## Use Again



### Repack and remanufacture

|                                 |                                                                                                                                                                                                                 |
|---------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Recyclability potential, in %   | 71                                                                                                                                                                                                              |
| End of life manual availability | <a href="#">End of Life Information</a>                                                                                                                                                                         |
| Take-back                       | Yes                                                                                                                                                                                                             |
| WEEE Label                      |  The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |

