

Product datasheet

Specifications



Sensor Module, TeSys Tera, CTVT Horizontal 0.3 to 3A, 690V, W110mm, inbuilt I/P for ZCT, SIDE Connector, Motor Management

LTMTCTV3UT

! Discontinued

EAN Code: 3606486392645

Main

Range	TeSys
Product name	TeSys Tera
Device short name	LTMT
Product or component type	Sensor
Device application	Motor protection

Complementary

[Ui] rated insulation voltage	690 V conforming to EN/IEC 60947-1
Overvoltage category	III
Pollution degree	3
[In] rated current	0.3...3 A at 60...690 V, AC 45...65 Hz
[Uimp] rated impulse withstand voltage	6 kV current or voltage measurement circuit
Protection type	Overload protection Stalled rotor Locked rotor Short-circuit Undercurrent Overcurrent Current unbalance Phase reversal Phase loss Earth fault protection internal Earth fault protection external Excessive starting time Max number of start Undervoltage Overvoltage Voltage unbalance Underfrequency Overfrequency Reacceleration Communication failure Fail to stop Under power Over power Power factor variation Anti-backspin timer Block output
Short-circuit withstand	100 kA conforming to EN/IEC 60947-4-1
Measurement accuracy	+/- 1 % voltage +/- 1 % current
Mounting mode	Horizontal
Connection pitch	5.0 mm

Connections - terminals	Voltage circuit: connector0.2...2.5 mm ² (AWG 12...AWG 24)
Input type	Analog
Sensor type	Current sensor Voltage sensor
Electromagnetic compatibility	Immunity to radiated electromagnetic interference (in open air), level 3, 10 Vrms, conforming to EN/IEC 61000-4-3 Resistance to electrostatic discharge (in open air), level 3, 8 kV, conforming to EN/IEC 61000-4-2 Digital output: resistance to electrostatic discharge (on contact), level 3, 6 kV, conforming to EN/IEC 61000-4-2 Digital output: immunity to shock waves (common mode), 4 kV, conforming to EN/IEC 61000-4-5 24 V DC sensors: immunity to shock waves (common mode), 1 kV, conforming to EN/IEC 61000-4-5 100...240 V inputs: immunity to shock waves (common mode), 2 kV, conforming to EN/IEC 61000-4-5 Communication: immunity to shock waves (common mode), 2 kV, conforming to EN/IEC 61000-4-5 Temperature sensor: immunity to shock waves (common mode), 1 kV, conforming to EN/IEC 61000-4-5 Digital output: immunity to shock waves (serial mode), 2 kV, conforming to EN/IEC 61000-4-5 24 V DC sensors: immunity to shock waves (serial mode), level 3, 1 kV, conforming to EN/IEC 61000-4-5 100...240 V inputs: immunity to shock waves (serial mode), 1 kV, conforming to EN/IEC 61000-4-5 Temperature sensor: immunity to shock waves (serial mode), 0.5 kV, conforming to EN/IEC 61000-4-5 Immunity to radiated radio-electrical interference, level 3, 10 Vrms, conforming to EN/IEC 61000-4-6
Depth	60.5 mm
Height	63.9 mm
Width	129.8 mm
Tightening torque	Control circuit: 0.5 N.m - with screwdriver flat 3 mm

Environment

Product certifications	IEC UL cUL
Standards	EN/IEC 60947-4-1 UL/CSA 60947-4-1
Fire resistance	650 °C conforming to EN/IEC 60695-2-12 960 °C conforming to UL 94
Protective treatment	12 x 24 hour cycles conforming to EN/IEC 60068-2-30
Ambient air temperature for storage	-40...80 °C
Operating altitude	<= 2000 m without derating
Mechanical robustness	Shocks half sine wave acceleration: 15 Gn for 11 ms conforming to EN/IEC 60068-2-27 Vibrations mounted on symmetrical rail: 1 Gn, 5...300 Hz conforming to EN/IEC 60068-2-6 Vibrations plate mounted: 4 Gn, 5...300 Hz conforming to EN/IEC 60068-2-6
Ambient air temperature for operation	-20...70 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	6.5 cm
Package 1 Width	7.5 cm

Package 1 Length	14 cm
Package 1 Weight	213 g
Unit Type of Package 2	S01
Number of Units in Package 2	2
Package 2 Height	15 cm
Package 2 Width	15 cm
Package 2 Length	40 cm
Package 2 Weight	867 g
Unit Type of Package 3	P06
Number of Units in Package 3	96
Package 3 Height	1050 cm
Package 3 Width	93 cm
Package 3 Length	113 cm
Package 3 Weight	32.448 kg

Contractual warranty

Warranty (in months)	18
-----------------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	17 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	6 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0.2 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	10 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	0.4 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile

Use Better



Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
SCIP Number	19513c74-ff2c-46a1-b26d-ced86e9921d7
EU RoHS Directive	Compliant By Exemption
REACH Regulation	Reference contains Substances of Very High Concern above the threshold
Halogen-free status	Halogen free plastic parts product
PVC free	Yes
Silicone-free	Yes

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again




Repack and remanufacture

Recyclability potential, in %	2
End of life manual availability	End of Life Information
Take-back	No


Technical Illustration

Wiring diagram



Technical Illustration

User interface / product ON



A. USB to RS485 Interface Cable
B. HMI Cable



Technical Illustration

Assembly's dimensions

mm
[in]

