

# Product datasheet

Specifications



Circuit breaker ComPacT NSX400K.  
36kA at 800VAC. 10kA at 1000VAC.  
MicroLogic 2.3 trip unit. 250A. 3  
poles 3d

C40K32D250

Price: 25,402.33 ZAR

## Main

|                                                      |                                                                                                                       |
|------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------|
| Range                                                | ComPacT                                                                                                               |
| Range of product                                     | ComPact NSX400...630                                                                                                  |
| Device short name                                    | ComPacT NSX400K                                                                                                       |
| Product or component type                            | Circuit breaker                                                                                                       |
| Device application                                   | Special application                                                                                                   |
| Number of poles                                      | 3P                                                                                                                    |
| Protected poles description                          | 3t                                                                                                                    |
| [In] rated current                                   | 250 A at 40 °C                                                                                                        |
| [Ue] rated operational voltage                       | 800...1000 V AC 50/60 Hz                                                                                              |
| Network type                                         | AC                                                                                                                    |
| Network frequency                                    | 50/60 Hz                                                                                                              |
| Suitability for isolation                            | Yes conforming to EN/IEC 60947-2                                                                                      |
| Utilisation category                                 | Category A                                                                                                            |
| [Icu] rated ultimate short-circuit breaking capacity | 36 kA Icu at 800 V AC 50/60 Hz conforming to IEC 60947-2<br>10 kA Icu at 1000 V AC 50/60 Hz conforming to IEC 60947-2 |
| Performance level                                    | K 10 kA 1000 V AC                                                                                                     |
| Trip unit name                                       | MicroLogic 2.3                                                                                                        |
| Trip unit technology                                 | Electronic                                                                                                            |
| Trip unit protection functions                       | LSol                                                                                                                  |
| Control type                                         | Toggle                                                                                                                |
| Circuit breaker mounting mode                        | Fixed                                                                                                                 |

## Complementary

|                                                     |                                                                                                               |
|-----------------------------------------------------|---------------------------------------------------------------------------------------------------------------|
| [Ui] rated insulation voltage                       | 1000 V AC 50/60 Hz                                                                                            |
| [Uimp] rated impulse withstand voltage              | 8 kV                                                                                                          |
| [Ics] rated service short-circuit breaking capacity | 10 kA at 800 V AC 50/60 Hz conforming to IEC 60947-2<br>10 kA at 1000 V AC 50/60 Hz conforming to IEC 60947-2 |
| Mechanical durability                               | 15000 cycles                                                                                                  |
| Electrical durability                               | 1000 cycles at 1000 V In                                                                                      |
| Mounting support                                    | Backplate                                                                                                     |
| Upside connection                                   | Front                                                                                                         |
| Downside connection                                 | Front                                                                                                         |

Excluding VAT and subject to change. Please check with your local distributor through "Where to buy"

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

|                                                           |                                                                                                                                                            |
|-----------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Connection pitch                                          | 45 mm                                                                                                                                                      |
| Protection type                                           | L : for overload protection (long time)<br>So : for short time short-circuit protection with fixed delay<br>I : for instantaneous short-circuit protection |
| Trip unit rating                                          | 250 A at 40 °C                                                                                                                                             |
| Long-time pick-up adjustment type Ir (thermal protection) | Adjustable 9 settings                                                                                                                                      |
| [Ir] long-time protection pick-up adjustment range        | 70...250 A                                                                                                                                                 |
| Long-time protection delay adjustment type tr             | Fixed                                                                                                                                                      |
| [tr] long-time protection delay adjustment range          | 11 s at 7.2 x Ir<br>16 s at 6 x Ir<br>400 s at 1.5 x Ir                                                                                                    |
| Thermal memory                                            | 20 minutes before and after tripping                                                                                                                       |
| Short-time protection pick-up adjustment type Isd         | Adjustable 9 settings                                                                                                                                      |
| [Isd] Short-time protection pick-up adjustment range      | 1.5...10 x Ir                                                                                                                                              |
| Short-time protection delay adjustment type tsd           | Fixed                                                                                                                                                      |
| Instantaneous protection pick-up adjustment type Ii       | Fixed                                                                                                                                                      |
| [Ii] instantaneous protection pick-up adjustment range    | 3000 A                                                                                                                                                     |
| Earth-leakage protection                                  | Without                                                                                                                                                    |
| Zone selective interlocking ZSI                           | Without                                                                                                                                                    |
| Number of slots for electrical auxiliaries                | 6 slot(s)                                                                                                                                                  |
| Local signalling                                          | Flashing LED (green) for ready to operate<br>LED 105 % Ir (red) for overload<br>LED 90 % Ir (orange) for overload                                          |
| Width (W)                                                 | 140 mm                                                                                                                                                     |
| Height (H)                                                | 255 mm                                                                                                                                                     |
| Depth (D)                                                 | 110 mm                                                                                                                                                     |
| Net weight                                                | 6.05 kg                                                                                                                                                    |

## Environment

|                                       |                                                              |
|---------------------------------------|--------------------------------------------------------------|
| Standards                             | EN/IEC 60947                                                 |
| Product certifications                | CE<br>CCC                                                    |
| Electrical shock protection class     | Class II                                                     |
| Pollution degree                      | 3 conforming to IEC 60664-1                                  |
| IP degree of protection               | IP40 conforming to IEC 60529                                 |
| IK degree of protection               | IK07 conforming to IEC 62262                                 |
| Ambient air temperature for operation | -25...70 °C                                                  |
| Ambient air temperature for storage   | -50...85 °C                                                  |
| Relative humidity                     | 0...95 %                                                     |
| Operating altitude                    | 0...2000 m without derating<br>2000 m...5000 m with derating |

## Packing Units

|                              |         |
|------------------------------|---------|
| Unit Type of Package 1       | PCE     |
| Number of Units in Package 1 | 1       |
| Package 1 Height             | 17.1 cm |
| Package 1 Width              | 17.6 cm |
| Package 1 Length             | 30.0 cm |
| Package 1 Weight             | 5.7 kg  |

## Contractual warranty

|                      |    |
|----------------------|----|
| Warranty (in months) | 18 |
|----------------------|----|



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



### Environmental footprint

|                                                        |                                               |
|--------------------------------------------------------|-----------------------------------------------|
| Total lifecycle Carbon footprint                       | 174 kg CO2 eq.                                |
| Environmental Disclosure                               | <a href="#">Product Environmental Profile</a> |
| Carbon footprint of the manufacturing phase [A1 to A3] | 39 kg CO2 eq.                                 |
| Carbon footprint of the distribution phase [A4]        | 1 kg CO2 eq.                                  |
| Carbon footprint of the installation phase [A5]        | 0.6 kg CO2 eq.                                |
| Carbon footprint of the use phase [B2, B3, B4, B6]     | 121 kg CO2 eq.                                |
| Carbon footprint of the end-of-life phase [C1 to C4]   | 12 kg CO2 eq.                                 |

## Use Better



### Materials and Substances

|                                        |                                           |
|----------------------------------------|-------------------------------------------|
| Packaging made with recycled cardboard | Yes                                       |
| Packaging without single use plastic   | Yes                                       |
| <a href="#">EU RoHS Directive</a>      | Compliant with Exemptions                 |
| SCIP Number                            | 25ca3248-85d0-423a-a9d8-5b7aeb52e7b6      |
| REACH Regulation                       | <a href="#">REACH Declaration</a>         |
| Halogen-free status                    | Product contains halogen above thresholds |
| PVC free                               | Yes                                       |
| Silicone-free                          | No                                        |

## Use Longer



### Lifetime extension

|              |    |
|--------------|----|
| Repair       | No |
| Updatability | No |

## Use Again



### Repack and remanufacture

|                                 |                                                                                                                                                                                                                 |
|---------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Recyclability potential, in %   | 56                                                                                                                                                                                                              |
| End of life manual availability | <a href="#">End of Life Information</a>                                                                                                                                                                         |
| Take-back                       | No                                                                                                                                                                                                              |
| WEEE Label                      |  The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |

