

Product datasheet

Specifications



switch-disconnector Masterpact NT08HA - 800 A - 690 V - 3 poles - drawout

47250

Main

Range	MasterPacT
Product name	MasterPact NT
Product or component type	Switch disconnector
Device short name	MasterPact NT08
Switch-disconnector name	MasterPact NT08HA
Device application	Protection
Poles description	3P
Network type	AC
Network frequency	50/60 Hz
[Ie] rated operational current	800 A AC 50/60 Hz 690 V
[Ui] rated insulation voltage	1000 V AC 50/60 Hz conforming to IEC 60947-3
[Uimp] rated impulse withstand voltage	12 kV conforming to IEC 60947-3
[Icm] rated short-circuit making capacity	75 kA 220...690 V AC at 50/60 Hz
[Ue] rated operational voltage	690 V AC 50/60 Hz conforming to IEC 60947-3
Breaking capacity code	HA
Suitability for isolation	Yes conforming to IEC 60947-3
Contact position indicator	Yes
Visible break	No
Pollution degree	3 conforming to IEC 60664-1

Complementary

Control type	Push-button
Mounting mode	Drawout
Mounting support	Chassis
Upside connection	Front
Downside connection	Front
Operating rate	10 cyc/h maximum
[Icw] rated short-time withstand current	36 kA during 0.5 s conforming to IEC 60947-3 36 kA during 1 s conforming to IEC 60947-3 20 kA during 3 s conforming to IEC 60947-3
Mechanical durability	12500 cycles without maintenance conforming to IEC 60947-3

Excluding VAT, FCA Jabal Ali & are subject to change – check with your local distributor.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Electrical durability	AC-23A: 3000 cycles 690 V AC 50/60 Hz without maintenance conforming to IEC 60947-3 AC-23A: 6000 cycles 440 V AC 50/60 Hz without maintenance conforming to IEC 60947-3 AC-3: 6000 cycles 440 V AC 50/60 Hz without maintenance conforming to IEC 60947-3
Connection pitch	70 mm
Height	301 mm
Width	276 mm
Depth	196 mm
Product weight	14 kg

Environment

Standards	IEC 60947-3
Product certifications	LCIE ASEFA
Ambient air temperature for operation	-5...70 °C
Ambient air temperature for storage	-40...85 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	36.000 cm
Package 1 Width	23.000 cm
Package 1 Length	39.000 cm
Package 1 Weight	14.279 kg
Unit Type of Package 2	P12
Number of Units in Package 2	8
Package 2 Height	90.000 cm
Package 2 Width	80.000 cm
Package 2 Length	120.000 cm
Package 2 Weight	129.832 kg

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	921 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	283 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	6 kg CO2 eq.
Carbon footprint of the installation phase [A5]	22 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	547 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	64 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile

Use Better



Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No, we have minimized the use of plastic in the packaging in compliance with regulations and considering quality and safety standards
SCIP Number	27fdc503-4522-4881-a1c6-58cfc3a5b0b0
EU RoHS Directive	Compliant By Exemption
REACH Regulation	Reference contains Substances of Very High Concern above the threshold
Halogen-free status	Halogen free plastic parts product
PVC free	Yes
Silicone-free	No

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Recyclability potential, in %	70
End of life manual availability	End of Life Information
Take-back	No
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

