

# Product datasheet

Specifications



circuit breaker ComPact NSX160F  
AC/DC, 18 kA at 240 VAC, TMD trip  
unit 125 A, 1 pole 1d

LV438669

⚠ Discontinued on: 31 Mar 2022

⚠ Discontinued

## Main

|                                                      |                                                                                                                                                                          |
|------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Range                                                | ComPact                                                                                                                                                                  |
| Product name                                         | ComPact NSX                                                                                                                                                              |
| Range of product                                     | ComPact NSX100...250 DC<br>ComPact NSX100...250                                                                                                                          |
| Device short name                                    | NSX160F                                                                                                                                                                  |
| Product or component type                            | Circuit breaker                                                                                                                                                          |
| Device application                                   | Distribution                                                                                                                                                             |
| Number of poles                                      | 1P                                                                                                                                                                       |
| Protected poles description                          | 1t                                                                                                                                                                       |
| [In] rated current                                   | 125 A at 40 °C                                                                                                                                                           |
| [Ue] rated operational voltage                       | 250 V DC<br>277 V AC 50/60 Hz                                                                                                                                            |
| Network type                                         | DC<br>AC                                                                                                                                                                 |
| Network frequency                                    | 50/60 Hz                                                                                                                                                                 |
| Suitability for isolation                            | Yes conforming to EN/IEC 60947-2                                                                                                                                         |
| Utilisation category                                 | Category A                                                                                                                                                               |
| [Icu] rated ultimate short-circuit breaking capacity | 36 kA Icu at 250 V DC 1P conforming to IEC 60947-2<br>36 kA Icu at 125 V DC 1P conforming to IEC 60947-2<br>18 kA Icu at 220/240 V AC 50/60 Hz conforming to IEC 60947-2 |
| Performance level                                    | F 18 kA 240 V AC                                                                                                                                                         |
| Trip unit name                                       | TM-D                                                                                                                                                                     |
| Trip unit technology                                 | Thermal-magnetic                                                                                                                                                         |
| Control type                                         | Toggle                                                                                                                                                                   |
| Circuit breaker mounting mode                        | Fixed                                                                                                                                                                    |

## Complementary

|                                                     |                                                                                                                                                        |
|-----------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------|
| [Ui] rated insulation voltage                       | 750 V AC 50/60 Hz conforming to IEC 60947-2                                                                                                            |
| [Uimp] rated impulse withstand voltage              | 8 kV conforming to IEC 60947-2                                                                                                                         |
| [Ics] rated service short-circuit breaking capacity | 36 kA at 250 V DC conforming to IEC 60947-2<br>36 kA at 125 V DC conforming to IEC 60947-2<br>18 kA at 220/240 V AC 50/60 Hz conforming to IEC 60947-2 |
| Mechanical durability                               | 20000 cycles                                                                                                                                           |

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

|                                                           |                                                                              |
|-----------------------------------------------------------|------------------------------------------------------------------------------|
| Electrical durability                                     | 10000 cycles at 277 V In<br>20000 cycles at 277 V In/2                       |
| Mounting support                                          | Backplate                                                                    |
| Upside connection                                         | Front                                                                        |
| Downside connection                                       | Front                                                                        |
| Connection pitch                                          | 35 mm                                                                        |
| Protection type                                           | for overload protection (thermal)<br>for short-circuit protection (magnetic) |
| Trip unit rating                                          | 125 A at 40 °C                                                               |
| Long-time pick-up adjustment type Ir (thermal protection) | Fixed                                                                        |
| [Ir] long-time protection pick-up adjustment range        | 1 In                                                                         |
| [Im] magnetic protection pick-up range                    | 1000 A                                                                       |
| Earth-leakage protection                                  | Without                                                                      |
| Width (W)                                                 | 35 mm                                                                        |
| Height (H)                                                | 161 mm                                                                       |
| Depth (D)                                                 | 86 mm                                                                        |

## Environment

|                                       |                                                              |
|---------------------------------------|--------------------------------------------------------------|
| Standards                             | EN/IEC 60947                                                 |
| Product certifications                | CCC<br>EAC<br>Marine                                         |
| Overvoltage category                  | Class II                                                     |
| Electrical shock protection class     | Class II                                                     |
| Pollution degree                      | 3 conforming to IEC 60664-1                                  |
| IP degree of protection               | IP40 conforming to IEC 60529                                 |
| IK degree of protection               | IK07 conforming to IEC 62262                                 |
| Ambient air temperature for operation | -25...70 °C                                                  |
| Ambient air temperature for storage   | -50...85 °C                                                  |
| Relative humidity                     | 0...95 %                                                     |
| Operating altitude                    | 0...2000 m without derating<br>2000 m...5000 m with derating |

## Packing Units

|                              |         |
|------------------------------|---------|
| Unit Type of Package 1       | PCE     |
| Number of Units in Package 1 | 1       |
| Package 1 Height             | 4.0 cm  |
| Package 1 Width              | 13.0 cm |
| Package 1 Length             | 17.5 cm |
| Package 1 Weight             | 739.0 g |
| Unit Type of Package 2       | S03     |
| Number of Units in Package 2 | 12      |
| Package 2 Height             | 30.0 cm |

|                  |          |
|------------------|----------|
| Package 2 Width  | 30.0 cm  |
| Package 2 Length | 40.0 cm  |
| Package 2 Weight | 9.355 kg |

## Contractual warranty

|                      |    |
|----------------------|----|
| Warranty (in months) | 18 |
|----------------------|----|



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



### Environmental footprint

|                                                        |                                               |
|--------------------------------------------------------|-----------------------------------------------|
| Total lifecycle Carbon footprint                       | 148 kg CO2 eq.                                |
| Carbon footprint of the manufacturing phase [A1 to A3] | 4 kg CO2 eq.                                  |
| Carbon footprint of the distribution phase [A4]        | 0.2 kg CO2 eq.                                |
| Carbon footprint of the installation phase [A5]        | 0.1 kg CO2 eq.                                |
| Carbon footprint of the use phase [B2, B3, B4, B6]     | 144 kg CO2 eq.                                |
| Carbon footprint of the end-of-life phase [C1 to C4]   | 0.1 kg CO2 eq.                                |
| Environmental Disclosure                               | <a href="#">Product Environmental Profile</a> |

## Use Better



### Materials and Substances

|                   |                                        |
|-------------------|----------------------------------------|
| SCIP Number       | 3874e08b-fcb8-4aa9-87c4-d36abebf2833   |
| EU RoHS Directive | <a href="#">Compliant By Exemption</a> |

## Use Longer



### Lifetime extension

|        |    |
|--------|----|
| Repair | No |
|--------|----|

## Use Again



### Repack and remanufacture

|                                 |                                                                                                                                                                                                                 |
|---------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| End of life manual availability | <a href="#">End of Life Information</a>                                                                                                                                                                         |
| WEEE Label                      |  The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |