

Product datasheet

Specifications



switch-disconnector Interpact INSJ400 - 4 poles - 400 A

31137

⚠ Discontinued on: 1 Nov 2020

⚠ Discontinued

Main

Range	ComPact
Product name	INSJ400
Switch-disconnector name	Interpact INSJ400
Poles description	4P
Network type	AC
Network frequency	50/60 Hz
[Ie] rated operational current	400 A AC 50/60 Hz 600 V
[Uimp] rated impulse withstand voltage	8 kV
[Icm] rated short-circuit making capacity	100 kA protected by circuit breaker NSJ400 - 400A 480 V AC at 50/60 Hz 150 kA protected by circuit breaker NSJ400 - 400A 240 V AC at 50/60 Hz 20 kA protected by any protection device 600 V AC at 50/60 Hz 25 kA protected by circuit breaker NSJ400 - 400A 600 V AC at 50/60 Hz 50 kA with class T or RK fuses 400 A 600 V AC at 50/60 Hz
[Ue] rated operational voltage	600 V AC 50/60 Hz
Suitability for isolation	Yes
Contact position indicator	Yes

Complementary

Control type	Rotary handle
Mounting mode	Fixed
Mounting support	Plate
Upside connection	Front
Downside connection	Rear Front
Mechanical durability	5000 cycles conforming to UL 489
Electrical durability	1000 cycles full load
Height	205 mm
Width	185 mm
Depth	130 mm
Net weight	4.6 kg

Environment

Standards	UL 489 CSA C22.2 No 5.2
-----------	----------------------------

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	18.5 cm
Package 1 Width	18 cm
Package 1 Length	20.7 cm
Package 1 Weight	4.9 kg

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better



Materials and Substances

EU RoHS Directive

[Compliant](#)

Use Longer



Lifetime extension

Repair

No

Use Again



Repack and remanufacture

WEEE Label



The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins