

# Product data sheet

Specifications



## TeSys F contactor - 4P (4 NO) - AC-1 - $\leq 440$ V 200 A - coil 380 V AC

LC1F1154Q7

⚠ Discontinued on: Dec 30, 2024

⚠ Discontinued

### Main

|                                |   |
|--------------------------------|---|
| Range                          | TeSys   |
| Range of product               | TeSys F   |
| Product or component type      | Contactor   |
| Device short name              | LC1F  |
| Contactor application          | Resistive load                                    |
| Utilisation category           | AC-1  |
| Poles description              | 4P  |
| [Ue] rated operational voltage | $\leq 690$ V AC 50/60 Hz<br>$\leq 460$ V DC       |
| [Uc] control circuit voltage   | 380 V AC 40...400 Hz                              |
| [Ie] rated operational current | 200 A (at $<104$ °F (40 °C)) at $\leq 440$ V AC-1 |

### Complementary

|   |  |
|---|--|
| [Uimp] rated impulse withstand voltage      | 8 kV   |
| [Ith] conventional free air thermal current | 200 A (at $104$ °F (40 °C))  |
| Rated breaking capacity                     | 920 A conforming to IEC 60947-4-1  |
| [Icw] rated short-time withstand current    | 1100 A $104$ °F (40 °C) - 10 s<br>640 A $104$ °F (40 °C) - 30 s<br>520 A $104$ °F (40 °C) - 1 min<br>400 A $104$ °F (40 °C) - 3 min<br>320 A $104$ °F (40 °C) - 10 min |
| Associated fuse rating                      | 125 A aM at $\leq 440$ V<br>200 A gG at $\leq 440$ V   |
| Average impedance                           | 0.37 mOhm - Ith 200 A 50 Hz  |
| [Ui] rated insulation voltage               | 1000 V IEC 60947-4-1<br>1500 V VDE 0110 group C  |
| Power dissipation per pole                  | 15 W AC-1  |
| Overvoltage category                        | III  |
| power pole contact composition              | 4 NO   |
| Control circuit voltage limits              | Operational 0.85...1.1 Uc 40...400 Hz $131$ °F (55 °C)<br>Drop-out 0.2...0.55 Uc 40...400 Hz $131$ °F (55 °C)  |
| Mechanical durability                       | 10 Mcycles   |
| Inrush power in VA                          | 770 VA, 40...400 Hz 0.9 $68$ °F (20 °C))   |
| Hold-in power consumption in VA             | 8.1 VA, 40...400 Hz 0.9 $68$ °F (20 °C))   |

|                                |  |
|--------------------------------|--|
| <b>Maximum operating rate</b>  | 2400 cyc/h 131 °F (55 °C)  |
| <b>Operating time</b>          | 35 ms closing at Uc)<br>130 ms opening at Uc)  |
| <b>Connections - terminals</b> | Power circuit bar 2 20 x 3 mm<br>Power circuit lugs-ring terminals 1 0.1 in <sup>2</sup> (95 mm <sup>2</sup> )<br>Power circuit connector 1 0.1 in <sup>2</sup> (95 mm <sup>2</sup> )<br>Control circuit screw clamp terminals 1 0.002...0.006 in <sup>2</sup> (1...4 mm <sup>2</sup> )flexible without cable end<br>Control circuit screw clamp terminals 2 0.002...0.006 in <sup>2</sup> (1...4 mm <sup>2</sup> )flexible without cable end<br>Control circuit screw clamp terminals 1 0.002...0.006 in <sup>2</sup> (1...4 mm <sup>2</sup> )flexible with cable end<br>Control circuit screw clamp terminals 2 0.002...0.004 in <sup>2</sup> (1...2.5 mm <sup>2</sup> )flexible with cable end<br>Control circuit screw clamp terminals 1 0.002...0.006 in <sup>2</sup> (1...4 mm <sup>2</sup> )solid without cable end<br>Control circuit screw clamp terminals 2 0.002...0.006 in <sup>2</sup> (1...4 mm <sup>2</sup> )solid without cable end<br>Power circuit bolted connection |
| <b>Tightening torque</b>       | Power circuit 88.5 lbf.in (10 N.m)<br>Control circuit 10.6 lbf.in (1.2 N.m)  |
| <b>Mounting support</b>        | Plate  |
| <b>Heat dissipation</b>        | 5.9...7.2 W  |
| <b>Standards</b>               | JIS C8201-4-1<br>EN 60947-1<br>EN 60947-4-1<br>IEC 60947-1<br>IEC 60947-4-1  |
| <b>Product certifications</b>  | UL<br>LROS (Lloyds register of shipping)<br>CB<br>ABS<br>CCC<br>RMRoS<br>RINA<br>DNV<br>BV<br>UKCA   |
| <b>Compatibility code</b>      | LC1F   |
| <b>Control circuit type</b>    | AC 40...400 Hz   |

## Environment

|  |   |
|--|---|
| <b>IP degree of protection</b>                               | IP2X front face with shrouds IEC 60529<br>IP2X front face with shrouds VDE 0106 |
| <b>Protective treatment</b>                                  | TH  |
| <b>Ambient air temperature for operation</b>                 | -40...140 °F (-40...60 °C)  |
| <b>Ambient air temperature for storage</b>                   | -76...176 °F (-60...80 °C)  |
| <b>Permissible ambient air temperature around the device</b> | 140...158 °F (60...70 °C) at Uc   |
| <b>Height</b>  | 6.4 in (162 mm)   |
| <b>Width</b>   | 7.9 in (200.5 mm)   |
| <b>Depth</b>   | 6.7 in (171 mm)   |
| <b>Operating altitude</b>                                    | 3000 m without derating   |
| <b>Net weight</b>  | 8.44 lb(US) (3.83 kg)   |

## Packing Units

|                               |     |
|-------------------------------|-----|
| <b>Unit Type of Package 1</b> | PCE |
|-------------------------------|-----|

---

|                                     |                        |
|-------------------------------------|------------------------|
| <b>Number of Units in Package 1</b> | 1                      |
| <b>Package 1 Height</b>             | 8.7 in (22.0 cm)       |
| <b>Package 1 Width</b>              | 8.5 in (21.5 cm)       |
| <b>Package 1 Length</b>             | 10.4 in (26.5 cm)      |
| <b>Package 1 Weight</b>             | 10.63 lb(US) (4.82 kg) |

---



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



### Environmental footprint

|  |   |
|--|---|
| Total lifecycle Carbon footprint                       | 823 kg CO2 eq.                                |
| Carbon footprint of the manufacturing phase [A1 to A3] | 78 kg CO2 eq.                                 |
| Carbon footprint of the distribution phase [A4]        | 0.8 kg CO2 eq.                                |
| Carbon footprint of the installation phase [A5]        | 0.4 kg CO2 eq.                                |
| Carbon footprint of the use phase [B2, B3, B4, B6]     | 736 kg CO2 eq.                                |
| Carbon footprint of the end-of-life phase [C1 to C4]   | 7 kg CO2 eq.                                  |
| Environmental Disclosure                               | <a href="#">Product Environmental Profile</a> |

### Use Better



### Materials and Substances

|  |  |
|--|--|
| Packaging made with recycled cardboard | Yes                                    |
| Packaging without single use plastic   | No                                     |
| SCIP Number                            | B2d4179a-eb65-40a3-a1ef-d9a33060486f   |
| EU RoHS Directive                      | <a href="#">Compliant By Exemption</a> |

### Use Longer



### Lifetime extension

|        |    |
|--------|----|
| Repair | No |
|--------|----|

### Use Again



### Repack and remanufacture

|                               |   |
|-------------------------------|---|
| Recyclability potential, in % | 91  |
| Take-back                     | No  |
| WEEE Label                    |  The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |