

Product datasheet

Specifications



steel enclosure IP66 for Compact INS200 with extended rotary handle

LV431228

⚠ Discontinued on: Aug 27, 2025

⚠ Discontinued

Main

Range of product	INS100...250
Product or component type	Enclose safety-switch
Accessory / separate part category	Enclosure accessory
Targeted country	Norway
Range compatibility	ComPact ComPacT INS INS250 switch disconnecter ComPact ComPacT INS INS200 switch disconnecter
enclosure type	Enclosure
Accessories included with enclosure	Rotary handle
Enclosure material	Steel

Complementary

Enclosure mounting	Surface
compatible devices	INS250 INS200
Control type	Extended rotary handle
Width	300 mm
Height	450 mm
Depth	200 mm

Environment

IP degree of protection	IP66 conforming to IEC 60529 IP40
IK degree of protection	IK08 IK07 conforming to EN 50102

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1

Contractual warranty

Warranty (in months)	18
----------------------	----

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained](#) >

[How we assess product sustainability](#) >

Use Better

Materials and Substances	
EU RoHS Directive	Compliant

Use Longer

Lifetime extension	
Repair	No

Use Again

Repack and remanufacture	
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins