


Product datasheet

Specifications



trip unit - STR22ME - 220 A - 3 poles 3d

31520

EAN Code: 3303430315209

! Discontinued

Main

Range	ComPact
Range of product	NS100...250
Product or component type	Trip unit
Trip unit name	STR22ME
Trip unit technology	Electronic
Range compatibility	ComPact NS250 ComPact NR100 ComPact NR250
Device application	Motor
Number of poles	3P
Protected poles description	3t
Protection type	for overload protection (long time) for short time short-circuit protection
Trip unit rated current	198 A at 70 °C 209 A at 60 °C 220 A at 20 °C
Network type	AC
Network frequency	50/60 Hz

Complementary

Long-time pick-up adjustment type Ir (thermal protection)	Adjustable 10 settings
[Ir] long-time protection pick-up adjustment range	0.6...1 x In
Long-time protection delay adjustment type tr	Fixed
[tr] long-time protection delay adjustment range	120...320 s at 1.5 x Ir 4...10 s at 7.2 x Ir 6...15 s at 6 x Ir
Short-time protection pick-up adjustment type Isd	Fixed
[Isd] Short-time protection pick-up adjustment range	13 x Ir
Short-time protection delay adjustment type tsd	Fixed
[tsd] Short-time protection delay adjustment range	0.01...0.06 s
Instantaneous protection pick-up adjustment type Ii	Fixed
Neutral protection settings	1 x Ir
Display type	LED

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Environment

Standards	IEC 60947-2
Product certifications	LCIE KEMA ASEFA ASTA
Pollution degree	3 conforming to IEC 60947
IP degree of protection	IP40 conforming to IEC 60529
Ambient air temperature for operation	-25...70 °C
Ambient air temperature for storage	-50...85 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Longer

Lifetime extension	
Repair	No

Use Again

Repack and remanufacture	
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins