

# Product data sheet

Specifications



## ASCO 2200 Load Bank

ASCOLBLV2200

! Discontinued on: Nov 20, 2023

! Discontinued

### Main

Product Type Resistive load bank

### Complementary

Voltage Rating	12/24 V DC 26/52 V DC
Capacity Rating	150 A
Load Step Resolution	1 A
Cooling System Rating	179534.5 Gal/hr(US) (679.6 m3/h)
Provided Equipment	Switch 2 On-Off front of enclosure LED 1 alarm indication front of enclosure Cooling fans
Enclosure Material	Aluminium Steel
Surface Finish	Polyester powder
Color	Gray
Connection Terminals	Twist-on front panel)
Length	19.5 in (495 mm)
Width	12.7 in (323.8 mm)
Height	13.5 in (342.9 mm)
Product Weight	30.005 lb(US) (13.61 kg)

### Environment

Ambient Air Temperature	-18...122 °F (-28...50 °C)
Standards	ISO 9001 NEMA

### Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	19.5 in (49.5 cm)
Package 1 Width	12.8 in (32.4 cm)
Package 1 Length	13.5 in (34.3 cm)
Package weight(Lbs)	30.005 lb(US) (13.61 kg)

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

# Contractual warranty

---

Warranty (in months)

18



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Use Better



#### Materials and Substances

Packaging made with recycled cardboard **Yes**

Packaging without single use plastic **No**

### Use Longer



#### Lifetime extension

Repair **No**