


# Product datasheet

Specifications



chassis, EasyPact NW, 2500A, H, CB, 3 Poles

ENW22314

## Main

|                           |                                             |
|---------------------------|---------------------------------------------|
| Range of product          | EasyPact NW                                 |
| Range                     | EasyPact                                    |
| Device short name         | ENW25H                                      |
| Product or component type | Chassis                                     |
| Device application        | Mounting                                    |
| Range compatibility       | EasyPact EasyPact NW ENW25H circuit breaker |
| Poles description         | 3P                                          |
| Breaking capacity code    | H                                           |

## Complementary

|                    |                 |
|--------------------|-----------------|
| Mounting mode      | Drawout         |
| [In] rated current | 2500 A at 40 °C |
| Product weight     | 45.164 kg       |
| Height             | 440 mm          |
| Width              | 400 mm          |
| Depth              | 445 mm          |

## Packing Units

|                              |           |
|------------------------------|-----------|
| Unit Type of Package 1       | PCE       |
| Number of Units in Package 1 | 1         |
| Package 1 Height             | 44.0 cm   |
| Package 1 Width              | 40.0 cm   |
| Package 1 Length             | 44.5 cm   |
| Package 1 Weight             | 60.664 kg |

## Contractual warranty

|                      |    |
|----------------------|----|
| Warranty (in months) | 18 |
|----------------------|----|

Excluding VAT, FCA Jabal Ali & are subject to change – check with your local distributor.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



### Environmental footprint

|                                                        |                                               |
|--------------------------------------------------------|-----------------------------------------------|
| Total lifecycle Carbon footprint                       | 6 610 kg CO2 eq.                              |
| Carbon footprint of the manufacturing phase [A1 to A3] | 249 kg CO2 eq.                                |
| Carbon footprint of the distribution phase [A4]        | 62 kg CO2 eq.                                 |
| Carbon footprint of the installation phase [A5]        | 3 kg CO2 eq.                                  |
| Carbon footprint of the use phase [B2, B3, B4, B6]     | 6 200 kg CO2 eq.                              |
| Carbon footprint of the end-of-life phase [C1 to C4]   | 97 kg CO2 eq.                                 |
| Environmental Disclosure                               | <a href="#">Product Environmental Profile</a> |

## Use Better



### Materials and Substances

|                                        |                                                                                                                                       |
|----------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------|
| Packaging made with recycled cardboard | Yes                                                                                                                                   |
| Packaging without single use plastic   | No, we have minimized the use of plastic in the packaging in compliance with regulations and considering quality and safety standards |
| SCIP Number                            | 3f2d539a-6ab5-46aa-8603-9354f4ae3294                                                                                                  |
| EU RoHS Directive                      | <a href="#">Compliant By Exemption</a>                                                                                                |
| REACH Regulation                       | <a href="#">Reference contains Substances of Very High Concern above the threshold</a>                                                |

## Use Longer



### Lifetime extension

|        |    |
|--------|----|
| Repair | No |
|--------|----|

## Use Again



### Repack and remanufacture

|                                 |                                         |
|---------------------------------|-----------------------------------------|
| Recyclability potential, in %   | 68                                      |
| End of life manual availability | <a href="#">End of Life Information</a> |
| Take-back                       | No                                      |

Offer Marketing Illustration

Product benefits / Features

### EasyPact NW

**NFC connectivity**

Offers easy monitoring and allows for proactive actions.

**Colour-coded health status bar**

Offers easy monitoring and allows for proactive actions.

**Simpler commissioning**

Achieve quick and simple commissioning through GPC and mobile EPD.



**Innovative front-end retrofit capability**

Enables upgrades in just 5 minutes, eliminating the need for shutdown.

**Detailed event logs**

Facilitates rapid fault diagnosis with easy access to detailed trip event records.

**Compact frame**

Optimizes switchboard footprints with a compact frame size, offering a higher breaking capacity of up to 66 kA.

17 May 2026

Schneider Electric

3