

Product datasheet

Specifications



motor-mechanism Compact MT400 - 48..60 V AC

32639

⚠ Discontinued on: 2 Apr 2021

⚠ Discontinued

Main

Device short name	Motor mechanism modules with SDE adapter
Product or component type	Motor mechanism
Device application	Automatic spring charging
Control type	Standard
[Uc] control circuit voltage	48...60 V AC 50/60 Hz
circuit breaker frame rated current	400 A

Complementary

Control signal type	Maintained Impulse
Maximum power consumption in VA	500 VA close 500 VA open
Provided equipment	SDE adaptor

Contractual warranty

Warranty (in months)	18
----------------------	----

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Longer

Lifetime extension	
Repair	No

Use Again

Repack and remanufacture	
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins