



miniature circuit breaker 400 V 6 kA, 3+N-pole C, 0.5 A, D=70 mm

| Model  |                                 |
|--|---------------------------------|
| product brand name   | SENTRON                         |
| product designation  | Miniature circuit breaker       |
| General technical data   |                                 |
| number of poles  | 4                               |
| design of pole   | 3P+N                            |
| tripping characteristic class  | C                               |
| mechanical service life (operating cycles) typical   | 10 000                          |
| overvoltage category   | 3                               |
| degree of pollution  | 3                               |
| Voltage  |                                 |
| type of voltage of the operating voltage   | AC                              |
| insulation voltage (U <sub>i</sub> )   |                                 |
| <ul style="list-style-type: none"> <li>with single-phase operation at AC rated value</li> <li>with multi-phase operation at AC rated value</li> </ul>  | 440 V                           |
|  | 440 V                           |
| <ul style="list-style-type: none"> <li>operational current                             <ul style="list-style-type: none"> <li>at 40 °C rated value</li> <li>at 50 °C rated value</li> <li>at 55 °C rated value</li> </ul> </li> <li>operational current at AC rated value</li> </ul> | 0.48 A                          |
|  | 0.45 A                          |
|  | 0.44 A                          |
|  | 0.5 A                           |
| Supply voltage   |                                 |
| supply voltage   |                                 |
| <ul style="list-style-type: none"> <li>at AC</li> </ul>  | 400 V                           |
| value range of the supply voltage frequency  | 50/60 Hz                        |
| Protection class   |                                 |
| protection class IP  | IP20, with connected conductors |
| Breaking Capacity  |                                 |
| switching capacity current   |                                 |
| <ul style="list-style-type: none"> <li>at DC according to IEC 60947-2 rated value</li> <li>according to EN 60898 rated value</li> <li>according to IEC 60947-2 rated value</li> </ul>  | 15 kA                           |
|  | 6 kA                            |
|  | 30 kA                           |
| energy limitation class  | 3                               |
| Dissipation  |                                 |
| power loss [W] for rated value of the current at AC in hot operating state per pole  | 0.8 W                           |
| suitability for operation  | Infrastructure / Industry       |
| Product details  |                                 |
| product feature touch protection   | Yes                             |

|   |  |
|---|--|
| <b>product component</b>  |  |
| • combined terminal top   | Yes  |
| • combined terminal bottom  | Yes  |
| • neutral conductor switching   | Yes  |
| <b>product feature properties for main switches in accordance with EN 60204-1</b>   | Yes  |
| <b>product feature halogen-free</b>   | Yes  |
| <b>product feature sealable</b>   | Yes  |
| <b>product feature silicon-free</b>   | Yes  |
| <b>product extension installable supplementary devices</b>                          | Yes  |
| <b>Product function</b>   |  |
| <b>set values setting current (Ii) for I-tripping</b>                               | 8  |
| <b>reference value setting current (Ii) for I-tripping</b>                          | x In   |
| <b>Short circuit</b>  |  |
| <b>short-circuit current breaking capacity (Icn)</b>                                |  |
| • at AC according to UL 1077 and CSA C22.2 No.235                                   | 5 kA   |
| <b>Connections</b>  |  |
| <b>connectable conductor cross-section solid</b>                                    |  |
| • minimum   | 0.75 mm <sup>2</sup>                                 |
| • maximum   | 35 mm <sup>2</sup>                                   |
| <b>connectable conductor cross-section stranded</b>                                 |  |
| • minimum   | 0.75 mm <sup>2</sup>                                 |
| • maximum   | 35 mm <sup>2</sup>                                   |
| <b>connectable conductor cross-section finely stranded with core end processing</b> |  |
| • minimum   | 0.75 mm <sup>2</sup>                                 |
| • maximum   | 25 mm <sup>2</sup>                                   |
| <b>AWG number as coded connectable conductor cross section</b>                      |  |
| • minimum   | 18   |
| • maximum   | 4  |
| <b>tightening torque [lbf-in] with screw-type terminals</b>                         |  |
| • minimum   | 22 lbf-in  |
| • maximum   | 31 lbf-in  |
| <b>tightening torque with screw-type terminals</b>                                  |  |
| • minimum   | 2.5 N·m  |
| • maximum   | 3.5 N·m  |
| <b>position of power supply cord</b>  | Any  |
| <b>Mechanical Design</b>  |  |
| <b>height</b>   | 90 mm  |
| <b>width</b>  | 72 mm  |
| <b>depth</b>  | 76 mm  |
| <b>installation depth</b>   | 70 mm  |
| <b>number of modular width units</b>  | 4  |
| <b>fastening method</b>   | DIN rail   |
| <b>mounting position</b>  | any  |
| <b>Net Weight</b>   | 636 g  |
| <b>Environmental conditions</b>   |  |
| <b>influence of the surrounding temperature</b>                                     | max. 95% RH up to 55°C                               |
| <b>standard</b>   | IEC / EN 60898-1, IEC / EN 60947-2 / UL1077          |
| <b>vibration resistance according to IEC 60068-2-6</b>                              | ±1mm at 5 to 25Hz; 50m/s <sup>2</sup> at 25 to 150Hz |
| <b>ambient temperature during operation</b>   |  |
| • minimum   | -25 °C   |
| • maximum   | 55 °C  |
| <b>ambient temperature during storage</b>   |  |
| • minimum   | -40 °C   |
| • maximum   | 75 °C  |
| <b>number of test cycles for environmental testing according to IEC 60068-2-30</b>  | 6  |
| <b>Approvals Certificates</b>   |  |

|             |                          |  |  |  |  |
|-------------|--------------------------|--|--|--|--|
| Environment | General Product Approval |  |  |  |  |
|-------------|--------------------------|--|--|--|--|

[Environmental Confirmations](#)



[Environmental Confirmations](#)



|                          |  |  |  |  |  |
|--------------------------|--|--|--|--|--|
| General Product Approval |  |  |  |  |  |
|--------------------------|--|--|--|--|--|



[Miscellaneous](#)



[Confirmation](#)



|                          |     |                   |                      |  |  |
|--------------------------|-----|-------------------|----------------------|--|--|
| General Product Approval | EMV | Test Certificates | Maritime application |  |  |
|--------------------------|-----|-------------------|----------------------|--|--|



[Miscellaneous](#)



|                      |       |  |  |  |  |
|----------------------|-------|--|--|--|--|
| Maritime application | other |  |  |  |  |
|----------------------|-------|--|--|--|--|



[Confirmation](#)

|                     |
|---------------------|
| Further information |
|---------------------|

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information for data generation and storage

<https://support.industry.siemens.com/cs/ww/en/view/109995012>

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mifb=5SY6605-7>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/5SY6605-7>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

[https://www.automation.siemens.com/bilddb/cax\\_en.aspx?mifb=5SY6605-7](https://www.automation.siemens.com/bilddb/cax_en.aspx?mifb=5SY6605-7)

CAX-Online-Generator

<https://www.siemens.com/cax>

Tender specifications

<https://www.siemens.com/specifications>

Characteristic curves

[https://curves.simaris.siemens.com/curves/<mmp\\_prod\\_noCOMP="HAUPT"></mmp\\_prod\\_no>](https://curves.simaris.siemens.com/curves/<mmp_prod_noCOMP=)





last modified:

8/6/2025 

