


Product datasheet

Specifications



MH3 servomotor, 140mm, 2 stacks, smooth Shaft, SinCos Singleturn 16, Brake, angular, IP65

MH31402P06F2200

⚠ Discontinued on: 9 Feb 2023

⚠ Discontinued

Main

Range compatibility	PacDrive 3
Device short name	MH3
Product or component type	Servo motor

Complementary

Maximum mechanical speed	4000 rpm
[Us] rated supply voltage	115...480 V
Network number of phases	Three phase
Continuous stall current	16.83 A
Continuous stall torque	18.5 N.m, 115...480 V, three phase
Continuous power	3730 W
Peak stall torque	55.5 N.m, 115...480 V, three phase
Nominal output power	1.71 W, 115 V 2.93 W, 230 V 3.73 W, 400 V 3.73 W, 480 V
Nominal torque	16.34 N.m for LXM52 at 14.87 mA, 115 V, three phase 14.0 N.m for LXM52 at 13.13 mA, 230 V, single phase 10.17 N.m for LXM52 at 9.76 mA, 400 V, three phase 10.17 N.m for LXM52 at 9.76 mA, 480 V, three phase 16.34 N.m for LXM62 at 14.87 mA, 115 V, single phase 14.0 N.m for LXM62 at 13.13 mA, 230 V, single phase 10.17 N.m for LXM62 at 9.76 mA, 400 V, three phase 10.17 N.m for LXM62 at 9.76 mA, 480 V, three phase
Nominal speed	1000 rpm for LXM52 at 14.87 mA, 115 V, single phase 2000 rpm for LXM52 at 13.13 mA, 230 V, single phase 3500 rpm for LXM52 at 9.76 mA, 400 V, three phase 3500 rpm for LXM52 at 9.76 mA, 480 V, three phase 1000 rpm for LXM62 at 14.87 mA, 115 V, single phase 2000 rpm for LXM62 at 13.13 mA, 230 V, single phase 3500 rpm for LXM62 at 9.76 mA, 400 V, three phase 3500 rpm for LXM62 at 9.76 mA, 480 V, three phase
Maximum current Irms	57.42 A
Shaft end	Smooth shaft
Second shaft	Without second shaft end
Shaft diameter	24 mm
Shaft length	50 mm
IP degree of protection	IP65 standard
Encoder type	Single turn SinCos Hiperface

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Speed feedback resolution	16 periods
Holding brake	With
Holding torque	18 N.m
Mounting support	International standard flange
Motor flange size	140 mm
Electrical connection	Rotatable right-angled connectors
Torque constant	1.1 N.m/A at 120 °C
Back emf constant	70.7 V/krpm
Number of motor poles	10
Rotor inertia	33.5 kg.cm²
Stator resistance	0.23 Ohm
Stator inductance	2.99 mH
Stator electrical time constant	13 ms
Maximum radial force Fr	2240 N at 1000 rpm 1780 N at 2000 rpm 1550 N at 3000 rpm
Brake pull-in power	18 W
Type of cooling	Natural convection
Length	227 mm
Centring collar diameter	130 mm
Centring collar depth	3.5 mm
Number of mounting holes	4
Mounting holes diameter	11 mm
Circle diameter of the mounting holes	165 mm
Product weight	14.3 kg
Sizing reference	MH31402P
Temperature copper hot	135 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	26.0 cm
Package 1 Width	20.0 cm
Package 1 Length	59.0 cm
Package 1 Weight	13.3 kg

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	2 590 kg CO2 eq.
----------------------------------	------------------

Use Better



Materials and Substances

EU RoHS Directive	Compliant By Exemption
-------------------	--

PVC free	Yes
----------	-----

Use Longer



Lifetime extension

Repair	No
--------	----