

Product data sheet

Specifications



enclosed DOL starter TeSys - GVNGC - 63 A

GVNGC0263

⚠ Discontinued on: Jul 24, 2022

⚠ Discontinued

Main

Range of product	TeSys
Device short name	GVNGC
Motor starter type	Non reversing
Product or component type	Enclosed DOL starter
Poles description	3P
Motor starter composition	With circuit breaker
Trip unit technology	Magnetic
Thermal protection adjustment range	63 A
Control type	Rotary handle black
Enclosure material	Polycarbonate

Complementary

[Ue] rated operational voltage	500 V
Breaking capacity	100 kA Icu at 220...230 V conforming to IEC 60947-2 15 kA Icu at 500 V conforming to IEC 60947-2 30 kA Icu at 440 V conforming to IEC 60947-2 50 kA Icu at 400...415 V conforming to IEC 60947-2
cable entry	2 x 40 mm ISO at top 2 x 40 mm ISO at bottom 2 x 32 mm ISO at bottom 2 x 32 mm ISO at top 2 x 25 mm ISO at top 2 x 20 mm ISO at bottom 2 x 25 mm ISO at bottom 2 x 20 mm ISO at top
Locking options description	Padlock in OFF position 1 to 3 padlocks Ø 8
Width	186.3 mm
Height	348 mm
Depth	237 mm
Net weight	2.45 kg

Environment

Standards	IEC 60439-1 VDE 0660-102 EN 60947 IEC 60947-4
IP degree of protection	IP40 conforming to IEC 60529



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Longer



Lifetime extension

Repair

No

Use Again



Repack and remanufacture

WEEE Label



The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins