


Product datasheet

Specifications

Motors



AC servo motor BDH - 14.1 N.m -
6000 rpm - key shaft - without brake
- IP54

BDH1084L12A2B

EAN Code: 3389118187153

! Discontinued

Main

Product or component type	AC servo motors
Component name	BDH
Continuous stall torque	14.1 N.m for LXM15MD40N4 3 phases
Peak stall torque	27.28 N.m for LXM15MD40N4 at 230 V 3 phases 27.28 N.m for LXM15MD40N4 at 400 V 3 phases
Nominal output power	2800 W for LXM15MD40N4 at 230 V 3 phases 4000 W for LXM15MD40N4 at 400 V 3 phases
Nominal torque	11.2 N.m for LXM15MD40N4 at 230 V 3 phases 9 N.m for LXM15MD40N4 at 400 V 3 phases
Nominal speed	2500 rpm for LXM15MD40N4 at 230 V 3 phases 4000 rpm for LXM15MD40N4 at 400 V 3 phases
Maximum mechanical speed	6000 rpm
Product compatibility	LXM15MD40N4 at 230 V 3 phases LXM15MD40N4 at 400 V 3 phases
Shaft end	Keyed
IP degree of protection	IP54
Encoder type	Absolute multiturn SinCos Hiperface
Speed feedback resolution	1048576 points/turn x 4096 turns
Holding brake	Without
Mounting support	NEMA flange
Electrical connection	Rotatable right-angled connectors
Number of poles	10

Complementary

Range compatibility	Lexium 15
Maximum current Irms	37.76 A
Torque constant	0.8 N.m/A at 120 °C
Back emf constant	51.3 V/krpm at 120 °C
Stator resistance	0.33 Ohm at 20 °C
Stator inductance	1.8 mH at 20 °C
Stator electrical time constant	5.45 ms at 20 °C

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Maximum radial force Fr	300 N at 6000 rpm
	325 N at 5000 rpm
	350 N at 4000 rpm
	375 N at 3000 rpm
	400 N at 2000 rpm
	425 N at 1000 rpm
Maximum axial force Fa	0.3 x Fr
Net weight	9 kg



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Longer

Lifetime extension	
Repair	No