

Data sheet for dv/dt filter plus VPL

Article No. : 6SL3000-2DH38-1AA0



Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Rated data	
------------	--

Output current	810 A
----------------	-------

General technical specifications		
----------------------------------	--	--

Power loss	dv/dt reactor	Voltage Peak Limiter (VPL)
at 690 V / 50 Hz	0.828 kW	0.106 kW
at 575 V / 60 Hz	0.867 kW	0.100 kW
at 690 V / 150 Hz	0.927 kW	0.091 kW

Connections	
-------------	--

Cable length	
--------------	--

for motor, max. (shielded)	300 m (984 ft)
for motor, max. (unshielded)	450 m (1,476 ft)

Design	dv/dt reactor	Voltage Peak Limiter (VPL)
Power cable	2 x hole for M12	-
Load	2 x hole for M12	-
PE conductor	M6 screw	M8 stud
dv/dt reactor	-	1 x hole for M10
DC link	-	1 x hole for M10

Mechanical data		
-----------------	--	--

Degree of protection	IP00	
----------------------	------	--

	dv/dt reactor	Voltage Peak Limiter (VPL)
Net weight	160 kg (353 lb)	72 kg (159 lb)

Dimensions		
------------	--	--

Width	445 mm (17.50 in)	309 mm (12.20 in)
Height	385 mm (15.20 in)	1,313 mm (51.70 in)
Depth	312 mm (12.30 in)	400 mm (15.70 in)

Standards	
-----------	--

Compliance with standards	CE, cURus
---------------------------	-----------