

product type designation



RF340R reader

SIMATIC RF300; Reader RF340R (GEN2); RS422 interface (3964R); IP67, -25 to +70 °C, 75x 75x 41 mm with integrated antenna .

product brand name	SIMATIC RF
Technical Product Detail Page	https://l.siemens.com/1P6GT2801-2BA10
suitability for operation	RF300, ISO 15693 and MOBY E transponder, for connecting to communication modules
radio frequencies	
operating frequency / rated value	13.56 MHz
range / maximum	140 mm; Range is dependent on transponder type: observe http://support.automation.siemens.com/WW/view/en/67384964
protocol / with radio transmission	RF300 specific, ISO 15693, ISO 18000-3, ISO 14443
transfer rate / with radio transmission / maximum	106 kbit/s
product feature / multitag-capable	No
electrical data	
transfer rate / at the point-to-point connection / serial / maximum	115.2 kbit/s
transmission time / for user data	
• for write access / per byte / typical	0.13 ms
• for read access / per byte / typical	0.13 ms
interfaces	
standard for interfaces / for communication	RS422
type of electrical connection	M12, 8-pin
mechanical data	
material	PA 12
color	titanium gray
tightening torque / of the screw for securing the equipment / maximum	1.5 N·m
mounting distance / relating to metal surfaces / recommended / minimum	0 mm
supply voltage, current consumption, power loss	
supply voltage / at DC	
• rated value	24 V
•	20.4 ... 28.8 V
consumed current / at DC	
• at 24 V / typical	0.06 A
ambient conditions	
ambient temperature	
• during operation	-25 ... +70 °C
• during storage	-40 ... +85 °C
• during transport	-40 ... +85 °C
protection class IP	IP67
shock resistance	EN 60721-3-7 Class 7 M2

shock acceleration	500 m/s ²
vibrational acceleration	200 m/s ²
design, dimensions and weights	
width	75 mm
height	41 mm
depth	75 mm
net weight	0.25 kg
fastening method	2 x M5 screws
wire length	
• for RS 422 interface / maximum	1000 m
product features, product functions, product components / general	
display version	5-color LED
product feature / silicon-free	Yes
standards, specifications, approvals	
certificate of suitability	Radio acc. to R&TTE guidelines EN 300 330, EN 301489, CE, FCC, cULus
certificate of suitability	
• IECEx	No
MTBF	260 a
standards, specifications, approvals / Environmental Product Declaration	
Environmental Product Declaration	Yes
global warming potential [CO ₂ eq]	
• total	50.4 kg
• during manufacturing	10.7 kg
• during operation	39.4 kg
• after end of life	0.3 kg
further information / internet links	
internet link	
• to website: Selection guide for cables and connectors	https://support.industry.siemens.com/cs/ww/en/view/109766358
• to web page: selection aid TIA Selection Tool	https://www.siemens.com/tstcloud
• to web page: RFID country approval	https://www.siemens.com/rfid-approvals
• to web page: identification and localization systems	https://www.siemens.com/ident
• to web page: SiePortal	https://sieportal.siemens.com/
• to website: Image database	https://www.automation.siemens.com/bilddb
• to website: CAX-Download-Manager	https://www.siemens.com/cax
• to website: Industry Online Support	https://support.industry.siemens.com
security information	
security information	Siemens provides products and solutions with industrial cybersecurity functions that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement - and continuously maintain - a holistic, state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit www.siemens.com/cybersecurity-industry . Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under https://www.siemens.com/cert . (V4.7)

Approvals / Certificates

General Product Approval



[China RoHS](#)



General Product Approval

Radio Equipment Type Approval Certificate

[Manufacturer Declaration](#)



[China RoHS](#)



[Industry Canada \(IC\)](#)

[Miscellaneous](#)

Radio Equipment Type Approval Certificate

Environment

[ECC](#)



[Miscellaneous](#)



last modified:

3/10/2026