



Main

Range	ComPact
Range of Product	ComPact NSX100...250
Device short name	Compact NSX250S
Product or Component Type	Basic frame
Device Application	Distribution
Circuit breaker name	Compact NSX250S
Number of poles	3P
Line Rated Current	250 A 104 °F (40 °C)
[Ue] rated operational voltage	690 V AC 50/60 Hz
Network type	AC
Network Frequency	50/60 Hz
Suitability for isolation	Yes EN/IEC 60947-2
Utilisation category	Category A
[Icu] rated ultimate short-circuit breaking capacity	100 KA Icu 380/415 V AC 50/60 Hz IEC 60947-2 120 KA Icu 220/240 V AC 50/60 Hz IEC 60947-2 15 KA Icu 660/690 V AC 50/60 Hz IEC 60947-2 40 KA Icu 525 V AC 50/60 Hz IEC 60947-2 65 KA Icu 500 V AC 50/60 Hz IEC 60947-2 90 KA Icu 440 V AC 50/60 Hz IEC 60947-2
Performance level	S 100 kA 415 V AC
Control Type	Toggle
Mounting Mode	Fixed

Complementary

[Ui] rated insulation voltage	800 V AC 50/60 Hz IEC 60947-2
[Uimp] rated impulse withstand voltage	8 kVIEC 60947-2
[Ics] rated service short-circuit breaking capacity	100 KA 380/415 V AC 50/60 Hz IEC 60947-2 120 KA 220/240 V AC 50/60 Hz IEC 60947-2 15 KA 660/690 V AC 50/60 Hz IEC 60947-2 40 KA 525 V AC 50/60 Hz IEC 60947-2 65 KA 500 V AC 50/60 Hz IEC 60947-2 90 KA 440 V AC 50/60 Hz IEC 60947-2
Mechanical durability	20000 cycles IEC 60947-2
Electrical durability	10000 Cycles 440 V AC 50/60 Hz In IEC 60947-2 10000 Cycles 690 V AC 50/60 Hz In/2 IEC 60947-2 20000 Cycles 440 V AC 50/60 Hz In/2 IEC 60947-2 5000 cycles 690 V AC 50/60 Hz In IEC 60947-2
Mounting Support	Backplate
Upside connection	Front
Downside connection	Front
Connection pitch	1.38 in (35 mm)
Protection Type	Without protection
Width (W)	4.13 in (105 mm)
Height (H)	6.34 in (161 mm)
Depth (D)	3.39 in (86 mm)

Environment

Standards	EN/IEC 60947-2 UL 508
Product Certifications	CSA UL
Pollution degree	3 IEC 60664-1
IP degree of protection	IP40 conforming to IEC 60529
IK degree of protection	IK07 IEC 62262
Ambient Air Temperature for Operation	-13...158 °F (-25...70 °C)
Ambient Air Temperature for Storage	-58...185 °F (-50...85 °C)

Ordering and shipping details

Category	01101-NF...E COMPACT NS IEC CIRCUIT BREAKERS, SWITCHES & MCP'S
Discount Schedule	DE2
GTIN	3606480006838
Returnability	No
Country of origin	PL

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.71 in (14.5 cm)
Package 1 Width	4.41 in (11.2 cm)
Package 1 Length	7.48 in (19.0 cm)
Package 1 Weight	3.55 lb(US) (1.61 kg)
Unit Type of Package 2	S04
Number of Units in Package 2	15
Package 2 Height	11.81 in (30.0 cm)
Package 2 Width	15.75 in (40.0 cm)
Package 2 Length	23.62 in (60.0 cm)
Package 2 Weight	54.86 lb(US) (24.886 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: DINP, which is known to the State of California to cause cancer, and DIDP, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Contractual warranty

Warranty	18 months
----------	-----------