

Product data sheet

Specifications

SQUARE D



DRUM SWITCH 600VAC 2HP A +OPTIONS

2601AG2S2F

! Discontinued

Main

Device Application	Manual reversing control
Device short name	A
Enclosure type	Standard environment enclosure indoor

Complementary

Depth	4.61 in (117.09 mm)
Device mounting	Flush
Electrical Connection	Screw clamp terminal
Height	5.38 in (136.65 mm)
Maximum Horse Power Rating	1.5 hp 115 V AC, 1 phase 2 hp 230 V AC, 1 phase 2 hp 200/575 V AC, 3 phase
Motor starter type	Reversing
Permissible voltage	600 V AC 250 V DC
Switch actuation	Maintained forward Momentary reverse
Type of operator	Fluted knob
Width	3.26 in (82.80 mm)

Environment

NEMA Degree of Protection	NEMA 1
Product Certifications	UL listed file E42243 CCN NLRV CSA LR25490 class 3211 05

Ordering and shipping details

Category	21116-2601
Discount Schedule	CP1
Returnability	No
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Package weight(Lbs)

21.60 oz (612.35 g)



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Longer



Lifetime extension

Repair

No