

Product data sheet

Specifications



SH3 servomotor, 100mm, 4 stacks, keyed Shaft, SinCos Multiturn 128, no Brake, angular, IP54/65

SH31004P12A2000

Product availability: Non-Stock - Not normally stocked in distribution facility

Main

Range Compatibility	PacDrive 3
Device short name	SH3
Product or Component Type	Servo motor

Complementary

Maximum mechanical speed	6000 rpm
[Us] rated supply voltage	115...480 V
Phase	Three phase
Continuous stall current	6.2 A
Continuous stall torque	88.5 lbf.in (10 N.m) 115...480 V three phase
Continuous power	2500 W
Peak stall torque	358.5 lbf.in (40.5 N.m) 115...480 V three phase
Nominal output power	780 W 115 V single phase 1490 W 230 V single phase 2480 W 400 V three phase 2600 W 480 V three phase
Nominal torque	87.6 lbf.in (9.9 N.m) 115 V single phase 84.08 lbf.in (9.5 N.m) 230 V single phase 69.9 lbf.in (7.9 N.m) 400 V three phase 61.07 lbf.in (6.9 N.m) 480 V three phase
Nominal speed	750 rpm 115 V single phase 1500 rpm 230 V single phase 3000 rpm 400 V three phase 3600 rpm 480 V three phase
Maximum current Irms	32.3 A
Shaft end	Parallel key
Shaft diameter	0.9 in (24 mm)
Shaft length	2.0 in (50 mm)
Key width	0.3 in (8 mm)
IP degree of protection	IP54 shaft bushing without shaft seal ring: conforming to IEC 60034-5 IP65 motor: conforming to IEC 60034-5 IP65 shaft bushing: conforming to IEC 60034-5
Encoder type	Absolute multiturn SinCos Hiperface
Speed feedback resolution	128 periods
Holding brake	Without
Mounting Support	International standard flange
Motor flange size	3.9 in (100 mm)

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Electrical Connection	Straight connector
Torque constant	1.62 N.m/A 248 °F (120 °C)
Back emf constant	103 V/krpm 68 °F (20 °C)
Number of motor poles	4.0
Rotor inertia	4.22 kg.cm²
Stator resistance	1.81 Ohm
Stator inductance	6.5 mH
Maximum radial force Fr	1070 N 1000 rpm 850 N 2000 rpm 740 N 3000 rpm
Maximum axial force Fa	160 N
Type of cooling	Natural convection
Length	10.9 in (276.5 mm)
Centring collar diameter	3.7 in (95 mm)
Centring collar depth	0.1 in (3.5 mm)
Number of mounting holes	4
Mounting holes diameter	0.4 in (9.0 mm)
Circle diameter of the mounting holes	4.5 in (115 mm)
Product Weight	20.3 lb(US) (9.2 kg)
Sizing reference	SH31004P
Network number of phases	3
Temperature copper hot	266 °F (130 °C)
Electrical connection	rotatable right angled connector
Output current 3s peak	32.3 A
Inertia	0.0 kg.cm² of brake 4.22 kg.cm² of motor

Ordering and shipping details

Category	US1PC5218359
Discount Schedule	PC52
GTIN	3606485297354
Returnability	Yes
Country of origin	DE

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	10.433 in (26.500 cm)
Package 1 Width	7.874 in (20.000 cm)
Package 1 Length	23.425 in (59.500 cm)
Package weight(Lbs)	23.484 lb(US) (10.652 kg)
Unit Type of Package 2	PAL

Number of Units in Package 2	8
Package 2 Height	33.465 in (85.000 cm)
Package 2 Width	33.465 in (85.000 cm)
Package 2 Length	25.591 in (65.000 cm)
Package 2 Weight	209.916 lb(US) (95.216 kg)

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	5 862 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	45 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	1 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0.1 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	5 815 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	1 kg CO2 eq.

Use Better



Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
SCIP Number	Ead0850d-370a-47c5-8cf7-1d93c2c974a4
EU RoHS Directive	Compliant By Exemption
REACH Regulation	Reference contains Substances of Very High Concern above the threshold
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
PVC free	Yes

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Circularity Profile	No need of specific recycling operations
Take-back	No