


# Product datasheet

Specifications



## TeSys F - contactor coil - LX0FF - 48 V AC/DC

LX0FF005

! Discontinued

### Main

Range	TeSys
Product or component type	Contactor coil
Device short name	LX0FF
Control circuit type	AC at 50...400 Hz DC standard
[Uc] control circuit voltage	48 V AC 50...400 Hz 48 V DC
Average resistance	1.98 Ohm latching at 20 °C 230.8 Ohm unlatching at 20 °C
Product compatibility	CR1F150
Operating time	35...40 ms latching 50...100 ms unlatching
Mechanical durability	1 Mcycles
Maximum operating rate	120 cyc/h 40 °C

### Complementary

Control circuit voltage limits	Latching: 0.85...1.1 Uc Unlatching: 0.85...1.1 Uc
--------------------------------	--

### Environment

Product weight	0.44 kg
----------------	---------

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1

### Contractual warranty

Warranty (in months)	18
----------------------	----

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Use Better



#### Materials and Substances

Packaging made with recycled cardboard **Yes**

Packaging without single use plastic **Yes**

### Use Longer



#### Lifetime extension

Repair **No**