


Product datasheet

Specifications



auxiliary contact - 1 SD - 240 V - 6 A

26928

⚠ Discontinued on: Jul 23, 2021

⚠ To be discontinued

Main

range of product	Multi9
Product or component type	Fault contact
Device short name	SD
Signal contacts composition	1 C/O
[In] rated current	AC-12 6 A at 220...240 V, AC 50/60 Hz DC-12 1 A at 130 V, DC DC-12 1.5 A at 60 V, DC DC-12 2 A at 48 V, DC AC-12 3 A at 277 V, AC 50/60 Hz DC-12 6 A at 12...24 V, DC
9 mm pitches	1
Standards	EN/IEC 60947-5-1
Product certifications	KEMA ASTA ASEFA LCIE

Complementary

Range compatibility	Multi9 C60 Multi9 C60H-DC Acti9 iSW-NA
Mounting mode	Fixed
Mounting support	DIN rail
Height	85 mm
Width	9 mm
Depth	73.5 mm
Connections - terminals	Pad terminal: 1 cable(s) 2.5 mm ² - rigid Pad terminal: 2 cable(s) 1.5 mm ² - rigid
Wire stripping length	9 mm
Tightening torque	1 N.m

Environment

IP degree of protection	IP20 conforming to EN/IEC 60947-5-1
Pollution degree	3 conforming to EN/IEC 60947-5-1
Tropicalisation	2 conforming to EN/IEC 60947-5-1
Relative humidity	95 % at 55 °C

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Ambient air temperature for operation	-25...50 °C
Ambient air temperature for storage	-40...85 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7.6 cm
Package 1 Width	1.9 cm
Package 1 Length	8.7 cm
Package 1 Weight	43 g

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

Materials and Substances	
Packaging made with recycled cardboard	Yes
EU RoHS Directive	Compliant

Use Longer

Lifetime extension	
Repair	No

Use Again

Repack and remanufacture	
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins