

Product datasheet

Specifications



resolver encoder interface module,
Altivar, 1 female SUB D9 connector

VW3AP3423

Main

Range of product	Altivar
Product or component type	Encoder interface module
Condition of use	Cannot be ordered alone, only possible in combination with a standard enclosure
Range compatibility	Altivar Process ATV900
Encoder type	Resolver

Complementary

Maximum supply current	0.05 A
Protection type	Short-circuit protection Overload protection
Maximum cable distance between devices	100 m
Maximum operating frequency	12 kHz
Input signal	Sin+, Sin-, Cos+, Cos-, Temp+, Temp-
Output signal	Ref+, Ref-
Ratio	3/10, 1/2, 3/4, 1
Connector type	1 female SUB-D 9
Product weight	0.15 kg

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	6.6 cm
Package 1 Width	13.0 cm
Package 1 Length	19.0 cm
Package 1 Weight	150.0 g

Contractual warranty

Warranty (in months)	18
----------------------	----

Excluding VAT, FCA Jabal Ali & are subject to change – check with your local distributor.



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

Materials and Substances	
Packaging made with recycled cardboard	No
Packaging without single use plastic	No

Use Longer

Lifetime extension	
Repair	No

Use Again

Repack and remanufacture	
Take-back	No