



Main

Range	TeSys
Device short name	GV3A
Product or component type	Auxiliary contact block
Product compatibility	GV3ME
Mounting location	Right side
Pole contact composition	2 NO
Connections - terminals	Screw clamp terminals 1 cable 0...0 in ² (1...2.5 mm ²) - cable stiffness: solid Screw clamp terminals 2 cable 0...0 in ² (1...2.5 mm ²) - cable stiffness: solid Screw clamp terminals 1 cable 0...0 in ² (0.75...2.5 mm ²) - cable stiffness: flexible - without cable end Screw clamp terminals 2 cable 0...0 in ² (0.75...2.5 mm ²) - cable stiffness: flexible - without cable end Screw clamp terminals 1 cable 0...0 in ² (0.75...2.5 mm ²) - cable stiffness: flexible - with cable end Screw clamp terminals 2 cable 0...0 in ² (0.75...1.5 mm ²) - cable stiffness: flexible - with cable end
Quantity per set	Set of 10

Complementary

[Ui] rated insulation voltage	600 V - conforming to UL 508 690 V - conforming to IEC 60947-1 600 V - conforming to CSA C22.2 No 14
System Voltage	48...690 V AC 24...220 V DC
[Ith] conventional free air thermal current	6 A
Protection type	GB2CB... circuit breaker rating according to operational current for Ue ≤ 415 V GG fuse ≤ 6 A
Mechanical durability	100000 cycles
Rated operational power in VA	350 VA at 48 V AC-11 - electrical durability: 100000 cycles 700 VA at 440 V AC-11 - electrical durability: 100000 cycles 700 VA at 500 V AC-11 - electrical durability: 100000 cycles 400 VA at 690 V AC-11 - electrical durability: 100000 cycles 500 VA at 110...127 V AC-11 - electrical durability: 100000 cycles 800 VA at 220...240 V AC-11 - electrical durability: 100000 cycles 850 VA at 380...415 V AC-11 - electrical durability: 100000 cycles
Rated operational power in W	180 W at 24 V DC-11 - electrical durability: 100000 cycles 240 W at 48 V DC-11 - electrical durability: 100000 cycles 180 W at 60 V DC-11 - electrical durability: 100000 cycles 140 W at 110 V DC-11 - electrical durability: 100000 cycles 120 W at 220 V DC-11 - electrical durability: 100000 cycles
Product weight	0.13 lb(US) (0.06 kg)

Environment

environmental characteristic	Normal environment
------------------------------	--------------------

Offer Sustainability

Green Premium product	Green Premium product
Compliant - since 0723 - Schneider Electric declaration of conformity	Compliant - since 0723 - Schneider Electric declaration of conformity
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold
Available	Available
Need no specific recycling operations	Need no specific recycling operations

WARNING: This product can expose you to chemicals including:	WARNING: This product can expose you to chemicals including:
Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm.	Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm.
For more information go to www.p65warnings.ca.gov	For more information go to www.p65warnings.ca.gov

Contractual warranty

Warranty period	18 months
-----------------	-----------